

DEPARTMENT OF MINES
SOUTH AUSTRALIA

REPORT ON BORE TWO AT CALCOOKRA

APPENDUM TO THE CHIEF MECHANICAL AND BORING ENGINEER'S
REPORT 549/50

This bore was situated 100 feet from Diamond drilling hole No. 1 on bearing of 55°.

Direction is on a bearing of 320° and depressed at an angle of 50°.

This hole was decided upon after careful consideration of the unpromising results of No. 1 bore which was not conductive to further drilling.

However, after further deliberation it was decided that in view of the old workings in close proximity to bore 1, there was a distinct possibility that the bore may have been worked out in this immediate area.

It was then decided that No. 2 bore should be drilled and work proceeded accordingly.

The No 2 bore concluded at 200'.
The Geological report is not to hand.

The total expenditure has now been assessed for this project and the cost for these two bores amounts to £4/15/- per foot, therefore the cost of the respective bores is No 1 bore £907/-/- No. 2 bore £950/-/- a total of £1,857/-/-

Details of costs are tabulated as under:-

Wages	£424/-/-	(£1/1/8 per foot)
On cost	£163/8/4	
Plant Rental	£153/7/10	
Stores	£243/12/6	
Cast Bits	£414/-/-	(£1/1/2 per foot)
<u>Other Costs:</u>		
Cartage	} £460/-/	(£1/3/6 per foot)
Travelling		
Camp Allowance		
Freight		

Total footage drilled on this project was 391'.

.....
D.M. WATSON
CHIEF MECHANICAL & BORING ENGINEER

KIB:RJM
28/5/53

MICROFILMED