DEPARTMENT OF HINES SOUTH AUSTRALIA

RIB 66/34.

WATER SUPPLY - PUTTAPA ZING PROSPECT

Grid J.S

- Flectrolytic Zinc Co. A/sin Ltd. -

by

R.K. JOIMS SUPERVISING GROLOGIST MINERAL RESOURCES DIVISION

CONTENTS	PAGE
INTRODUCTION	. 1
GEOLOGICAL SETTING	1
EXISTING WATER SUPPLIES	2
RECOMMENDATIONS	2
REFERENCES	3

P PLANS

rian No.	Title	<u>Seale</u>
68-104	Vater Supply - Puttapa Zinc Prespect (F.Z. Se.)	l mile = 1000 feet

Rept. Bk. No. 66/34 G.S. No. 3896 Hyd. No. 1974 D.H. 136/68

Rept. Ex. 50. 66/54 6.8. 50. 3696 Eyd. 50. 1974 D.H.136/60

VATUR SUDDLY - PUTTADA ZIRC PROSDECT

Grid J.S

- Electrolytic Zino Co. A/sis. Ltd. &

INTRODUCTION

In company with Er. I. HePaul (E.S. Co.) an inspection was undertaken on January 18th, 1968 to advise on the provision of a water supply at the Duttapa zinc prespect where exploration of a zinc-lead deposit is being conducted by the E.-S. Co. Small supplies of water are needed immediately for drilling and ablutions but when mining operations commence (possibly within 12 menths) the requirements will be much greater.

The deposite are located 8% miles due south of Copley and some 1% wiles east of the railway which connects Harroe and Port Augusta by standard gauge track.

GEOLOGICAL SETTING

Concentrations of sinc (as villemite) with lead, vanadium, manganese and iron occur as weathering residuals and replacement deposits with Cambrian Ajam Limestone in an area of
great structural disturbance. The accompanying plan (68-104)
shows the disposition of the various units of the Adelaide
System and succeeding Cambrian formations. The strate are contorted and often truncated by faults in a zone marginal to the
major Nor' Vest Pault.

MIISTING WATER SUPPLIES

Present supplies of water for dismend drilling purposes are drawn from Eunter Bore No.2 situated mean the northern boundary of Puttapa pasteral station. This 6 inch diameter bore drilled by the Department of Rines in 1953, is 146ft, deep and could to 126 ft. Vater containing 316 grains/gallon dissolved salts is drawn from sandatone-quartaite adjacent to a fault separating Pound Quartaite from Ajax Limestone. A 2-hour bailer test proved a supply in excess of 400 gallons/hour.

The abandened Ajax Bore, situated about 200 yards from the Ajax Copper Nine, was drilled by Horwood Engahaw Btd. for the E. & W.S. Dept. in 1943 to a depth of 103ft. 6 ins. The bere is reported to have intersected "disrite, delemite and quartaite" - apparently Caliana Bods to the east of the fault adjacent to the Ajax Nine. The water which contained 100 grains per gallon saline matter was tested at 1,000 gallons per day which is the same as that recorded from the main shaft of the Ajax Nine.

A high capacity supply might be provided from the Sliding Rook - Leigh Creek pipeline which passes within \$\foatiened\$ miles of the deposit. This formerly served as the enter supply for Leight Creek Coalfield prior to the construction of Arooma Dam. Salinity of this water, pumped from several boros at Sliding Rock, contained about \$5 grains/gallon.

RECOMMENDATIONS

As the company wish to preserve the existing pasteral water supply of Hunger's Here No.2 an alternative here site has been colocted adjacent to the creek 300 yards south east of the Ajax Hime. Boring to a depth of 150 ft. is expected to provide small supplies of potable water from the Ajax Limestone. The

rock is expected to be hard amuill require little casing.

A permanent high capacity water supply would be provided by the pipeline which commects Sliding Rock with Leigh Greek - this would require some 5 miles of piping to connect to the prospect, and the concurrence of the Electricity Trust of South Australia who maintain the line.

Magens

DHJ:0D 25.1.68 R.K. JOHNS
SUPERVISING GENAGEST
MINERAL RESOURCES DIVISION

RUPERUNCES

JOHNS, R.E. (1953) Underground Water Supplies, Futtapa Station (unpub.)

PARKEN, L.W. (1952) Copiey geological map (1 inch = 1 mile series)
WHITEHEAD, S. (1966) Report on Beltana Concessions (5ML 113, 136,
142) D.H. Env. 732 (Unpub.)

