DEPARTMENT OF MINES AND ENERGY SOUTH AUSTRALIA

REPT. BK. NO. 89/13

ANGAS BREMER IRRIGATION AREA OBSERVATION WELL DRILLING MARCH 1988

GEOLOGICAL SURVEY

by

S.R. HOWLES

FEBRUARY, 1989 DME 166/79

<u>CONTENTS</u>			<u>PAGE</u>
ABSTRACT			3
INTRODUCTION			3
DRILLING			3
RECOMMENDATIONS			4
			<u>Plan No</u>
Figure 1	location of Angas Bremer irrigation area	S20632	
Figure 2	location of observation wells	S20633	
Appendix A	Construction details		5
	DETAILS OF OBSERVATION WELL	6627-7829	
	DETAILS OF OBSERVATION WELL	6727-2311	
	DETAILS OF OBSERVATION WELL	6727-2313	
Appendix B Lithological logs			9
	LITHOLOGIC LOG OF OBSERVATION WELL	6627-7829	
	LITHOLOGIC LOG OF OBSERVATION WELL	6727-2311	
	LITHOLOGIC LOG OF OBSERVATION WELL	6727-2313	
Appendix C Full Analyses			10
	FULL ANALYSIS OF OBSERVATION WELL	6727-2311	

DEPARTMENT OF MINES AND ENERGY SOUTH AUSTRALIA

Rpt Bk No 89/13 DME No 166/79 Disk No E00064

ANGAS BREMER IRRIGATION AREA OBSERVATION WELL DRILLING MARCH 1988

S.R. HOWLES

ABSTRACT

Three new observation wells monitoring the Tertiay confined limestone aquifer underlying the Angas Bremer irrigation area have been completed.

INTRODUCTION

On-going hydrogeological investigations and data collection in the Angas Bremer irrigation area (Figure 1) require continued installation of observation wells. In March 1988 funds became available and three sites were chosen in consultation with J. Reed of the Water Resources Branch, Engineering and Water supply Department. These are considered to be of strategic importance for water level and salinity information for use in calibrating the computer model of the area. Extensive field checking failed to locate suitable alternative wells.

DRILLING

Drilling was carried out using the Departments Rotary Portadril from 9/3/88 to 12/3/88.

Drilling took place adjacent to:

Section 515 Hd of Bremer Section 328 Hd of Freeling Section 165 Hd of Freeling The intention being to install observation wells in the confined limestone aquifer underlying the area.

Locations of the observation wells at 1:50000 scale are are shown on Figure 2.

Details of the observation wells, lithological logs and full analysis are given in Appendix A, B and C, respectively.

RECOMMENDATIONS

Further drilling is recommended within the proclaimed area at sites to be determined by discussion with J. Reed where information vital for correct calibration of the computer modelling exercise is required.

SRH/HG <u>S. Howles</u>

Appendix A

Construction Details

Well specifications 6627-35-7829

observation No: BRM 180

permit No: 94902

Hundred: Bremer

Section: adj.515

completed: 10/3/88

total depth (m): 57

final depth (m): 57

casing type: PVC

casing diameter (mm): 100

casing interval (m): 0 - 45

linatex seal (m): 39

pressure cementing (m): 0 - 39

creen type: slotted PVC

screen interval (m): 45 - 51

screen apperture (mm): 1

aquifer monitored: confined limestone

final SWL (m): 17.22

final salinity (EC): 4000 (field)

estimated yield (L/s): 1

Well specifications 6727-30-2311

observation No: FRL 156

permit No: 94903

Hundred: Freeling

Section: adj.328

completed: 11/3/88

total depth (m): 28.7

final depth (m): 28.7

casing type: PVC

casing diameter (mm): 100

casing interval (m): 0 - 22.7

linatex seal (m): 16.7

pressure cementing (m): 0 - 16.7

screen type: slotted PVC

screen interval (m): 22.7 - 28.7

screen apperture (mm): 1

aquifer monitored: confined limestone

final SWL (m): 15.8

final salinity (mg/L): 9449

estimated yield (L/s): 0.5

Well specifications 6727-31-2313

observation No: FRL 158

permit No: 94904

Hundred: Freeling

Section: adj.165

completed: 12/3/88

total depth (m): 28

final depth (m): 28

casing type: PVC

casing diameter (mm): 100

casing interval (m): 0 - 22

linatex seal (m): 16

pressure cementing (m): 0 - 16

screen type: slotted PVC

screen interval (m): 22 - 28

screen apperture (mm): 1

aquifer monitored: confined limestone

final SWL (m): 8.8

final salinity (EC): 6000 (field)

estimated yield (L/s): --

Appendix B

Lithological logs

Appendix C

Full analyses



