

Open File Envelope

No. 3882

EL 632

NUNJIKOMPITA

**PROGRESS REPORTS FOR THE PERIOD
20/5/80 TO 19/11/80**

Submitted by

**Carpentaria Exploration Co. Pty Ltd
1980**

© open file date 24/9/85

This report was supplied as part of the requirement to hold a mineral or petroleum exploration tenement in the State of South Australia.
PIRSA accepts no responsibility for statements made, or conclusions drawn, in the report or for the quality of text or drawings.
This report is subject to copyright. Apart from fair dealing for the purposes of study, research, criticism or review as permitted under the Copyright Act, no part may be reproduced without written permission of the Chief Executive of Primary Industries and Resources South Australia, GPO Box 1671, Adelaide, SA 5001.

Enquiries: Customer Services
Ground Floor
101 Grenfell Street, Adelaide 5000

Telephone: (08) 8463 3000
Facsimile: (08) 8204 1880



**PRIMARY INDUSTRIES
AND RESOURCES SA**

CONTENTS ENVELOPE 3882Transparencies In
Cylinder 3882/1TENEMENT: E.L. 632 - Nunjikompita - S.E. Of Ceduna.TENEMENT HOLDER: Carpentaria Exploration Co. Pty. Ltd.REPORT: Progress Report For Quarter Ended 19th August 1980. Pgs. 3-4
Progress Report For Quarter Ended 19th November " Pgs. 5-75PLANS: Isopach Map Of Eocene Sediments. Drg. No. 15772. 3882-1
Pre-Eocene Basement Contours. Drg. No. 15771. 3882-2
Drill Hole Locations. Drg. No. 15770. 3882-3
Isopach Map Of Post-Eocene Sediments. Drg. No. 3882-4
15773.
Pre-Eocene Basement Contours. Drg. No. 15861. 3882-5

EXPLORATION LICENCE NO.632 "NUNJIKOMPITA"

PROGRESS REPORT FOR QUARTER ENDED AUGUST 19, 1980.

1. TERMS AND CONDITIONS

The Exploration Licence is located approximately 60 km east-south-east of Ceduna and covers an area of 2 251 km². The licence was granted for a term of one year commencing on May 20, 1980. The total expenditure requirement for the full term is \$70 000.

2. EXPLORATION


A series of rotary-mud holes have been drilled at two kilometre intervals along two traverses across the licence area to define the position of the Narlaby Channel. Drilling was carried out by two Mayhew 1000 rigs contracted from W.L. Sides and Son Ltd. during May and June of this year. A total of 3 618 m was drilled in 58 holes. Wire-line logging for gamma, self potential and resistivity was contracted to Geoex Pty. Ltd.

An isopach plan of Eocene sediments and a basement contour plan is currently being constructed together with a series of cross-sections. These will be forwarded together with the drill logs in the next Quarterly Report.

3. EXPENDITURE


A statement of expenditure is attached.

.....
P.J. Binks
Senior Geologist



CARPENTARIA EXPLORATION COMPANY PTY.LTD.EXPLORATION LICENCE NO. 632 "NUNJIKOMPITA"STATEMENT OF EXPENDITURE FOR QUARTER ENDED AUGUST 19,1980

	\$	\$
Administration	2 141	
Aerial Surveys	450	
Drilling	1 100	
Operating Labour	3 180	
Stores	482	
Transport	983	
Travelling Expenses	70	
<u>Total Expenditure This Period</u>		8 406
<u>TOTAL EXPENDITURE - CURRENT TERM</u>		\$ 8 406


.....
R.E. Darlington
Administration Manager.

CARPENTARIA EXPLORATION COMPANY PTY. LTD.

MINING TENEMENT

PROGRESS REPORT

EXPLORATION LICENCE NO.632 "NUNJIKOMPITA"

PROGRESS REPORT FOR QUARTER ENDED NOVEMBER 19, 1980



DATE: November, 1980

COPY: Department of Minerals & Energy

PROGRESS REPORT FOR QUARTER ENDED NOVEMBER 19, 1980.

1. TERMS AND CONDITIONS

The Exploration Licence is located approximately 60 km east-south-east of Ceduna and covers an area of 2 251 km². The Licence was granted for a term of one year commencing on May 20, 1980. The total expenditure requirement for the full term is \$70 000.

2. EXPLORATION

Completed drill logs from the drilling program previously reported together with an Eocene Isopach Plan (Drawing No. 15722) and Basement Contour Plan (Drawing No. 15771) are included with this report.

The drilling located the south-west extension of the Narlabay Channel which here is trending north-east to south-west. The channel is in excess of 6 km wide and contains up to 80 m of ?Eocene sediments. These comprise fine to coarse grained sand with interbedded black to grey brown clays. Overlying the channel sediments is up to 80 m of ?Pliocene fine grained sand and clayey silt.

Two drilling programs were completed on the area during the quarter. Thompson Drilling Pty. Ltd. drilled 8 holes for 202 m (IR 800-807 Drawing No. 15770) in the eastern part of the area. All the holes intersected a relatively shallow basement (maximum depth 36 m) with no palaeochannels located.

0007

2. EXPLORATION (CONT)

Another program of 21 drill holes totalling 1 852 m (IR 605-625 Drawing No. 15770) was completed by W.L. Sides & Son Pty. Ltd. Results from this drilling are currently being evaluated. Revised basement contours and isopach maps together with drill logs will be forwarded with the next report.

See Env 4010

3. EXPENDITURE

A statement of expenditure is attached.


.....
for G.J. Hooper
Project Geologist

CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 440

LOCATION: 36km. NW. Nunjikompita

ROTARY DRILL HOLE LOG

AIR: FROM..... TO.....

RL COLLAR:^m

CO-ORDS:

WATER: FROM...0.. TO..1.2m.....

A.M.G.:16800E,58800N...°

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log	0008
NOT LOGGED				CLAYEY SAND red brown, with calcrete, fine grained rounded quartz	
	10	SIL + + + + + +		SILCRETE silcreted coarse sand CLAY white clay with quartz and serecite	
	20				
	30				
	40				
	50				
	60				
	70				
	80				
	90				
	100				
	110				
	120				

SAMPLE Nos: 584682-584687

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY P. OWEN

DRILLER. W.L. SIDES

DATE DRILLED. 31/5/80

OTHER DETAILS

SCALE 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 441

ROTARY DRILL HOLE LOG

LOCATION: 34km NW Nunjikompita


AIR: FROM 0 TO 8m

RL COLLAR: 7

CO-ORDS:

WATER: FROM 0 TO

A.M.G.: 16800E, 57300N 0

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NOT LOGGED				CLAYEY SAND red brown, fine grained sub rounded quartz, with minor calcrete minor silcrete GRANITE VERY HARD
	10			
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 584688-584691

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 31/5/80

OTHER DETAILS:

SCALE: 1:500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 442

LOCATION: 33km NW Nunjikompita ROTARY DRILL HOLE LOG

AIR: FROM 0 TO 12m

RL COLLAR: m

CO-ORDS: WATER: FROM TO

A.M.G.: 16800E, 55400N. °

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NOT LOGGED				0010
				CLAYEY SAND yellow brown, with calcrete red brown yellow brown BASEMENT white feldspar with quartz, with silcreted sand at top
	10			
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 584692-584697

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY P. OWEN

DRILLER W.L. SIDES

DATE DRILLED: 31/5/80

OTHER DETAILS:

SCALE: 1:500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA

CARPENTARIA EXPLORATION COMPANY PTY. LTD.

LOCATION: 31.5km NW Nunjikompita

AIR: FROM 0 TO 12m

CO-ORDS:

WATER: FROM TO

HOLE N° IR 443

RL COLLAR: T

A.M.G: 16800E, 53500N .°

ROTARY DRILL HOLE LOG

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NOT LOGGED				0011
				SAND very fine grained, rounded quartz, yellow brown with calcrete
		SIL		SILCRETE silcreted sand with minor red brown clayey sand
	10	+		GRANITE white kaolinite and felds and quartz
		+		
		+		
		+		
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000

DRILLER: W.L. SIDES

SCALE: 1:500

LOGGED BY: P. OWEN

DATE DRILLED: 31/5/80

DRG./CODE No:

SAMPLE Nos: 584698-584703

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 444

ROTARY DRILL HOLE LOG

LOCATION: 30km NW Nunjikompita

AIR: FROM 0 TO 24m


RL COLLAR: 7

CO-ORDS:

WATER: FROM TO

A.M.G.: 16800E, 51600N

0012

Geophysical Log		Depth	Strip	Ox	Lithological Log
Type:	Geoex	Metres	Log		
		5			SAND very fine grained, rounded, yellow with calcrete
		10			red, with minor clay matrix with minor silcrete
		15	Sc		SAND fine grained, pinky red, with silcrete
		20	+		GRANITE with felds and quartz, pink felds
		25	+		
		30	+		
		35	+		
		40	+		
		45	+		
		50	+		
		55	+		
		60	+		
		65			
		70			
		75			
		80			
		85			
		90			
		95			
		100			
		105			
		110			
		115			
		120			

SAMPLE Nos: 584704-584715

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY P. OWEN

DRILLER W.L. SIDES

DATE DRILLED 31/5/80

OTHER DETAILS.

SCALE 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 445

ROTARY DRILL HOLE LOG

LOCATION: 28.5km NW Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....T.....

CO-ORDS:.....

WATER: FROM 0 TO 24m.....

A.M.G.: 16800E, 49400N. °

Geophysical Log		Depth	Strip	Ox	Lithological Log
Type:	Geoex	Metres	Log		
					0013
					CLAYEY SAND yellow brown with calcrete
					CLAYEY SILT yellow red brown
		10	SIL		SILCRETE cream, silcreted silt
					CLAYEY SILT orange brown, with silcreted silt bands
					with minor rounded quartz
		20			CLAY pinky white clay with minor quartz
		30			
		40			
		50			
		60			
		70			
		80			
		90			
		100			
		110			
		120			

SAMPLE Nos: 584716-584727

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

OTHER DETAILS

DRILLER: W.L. SIDES

DATE DRILLED: 31/5/80

SCALE 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 446

ROTARY DRILL HOLE LOG

LOCATION: 27.5km NW Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0... TO...36m.....

A.M.G: 16800E, 47800N.°.

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
				CLAYEY SAND yellow brown with silcrete
				SILTY CLAY red brown
				CLAY
				SILTY CLAY green grey, red brown
	10			SILTY CLAY with minor interbedded clays and silcretes and silts (brown)
				multicoloured reds and creams and browns
	20			CLAYEY SAND yellow brown, fine grained sand
				SAND medium grained, sub rounded quartz, yellow red
				with clay matrix
	30			CLAY pinky white with minor quartz
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 584728-584745

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY P. OWEN

DRILLER W.L. SIDES

DATE DRILLED 31/5/80

OTHER DETAILS:

SCALE: 1 500'

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 447

ROTARY DRILL HOLE LOG

LOCATION: 27km NW Nunjikompita


AIR: FROM TO

RL COLLAR: T.

CO-ORDS:

WATER: FROM 0 TO 50m

A.M.G.: 16900E, 45700N. P.

Geophysical Log Type: Geopex	Depth Metres	Strip Log	Ox	Lithological Log	0015
	5			CLAYEY SAND yellow brown, fine grained with calc.	
	10			SILTY CLAY red brown	
	15			SILCRETE cream and orange with ferricrete and minor cream green clays	
	20			CLAYEY SILTS cream to pink and red	
	25			SANDY CLAY cream red with minor silcrete	
	30			CLAYEY SAND yellow brown, fine grained rounded quartz	
	35			with minor cream and yellow clays and silty clays	
	40			with cream clay matrix	
	45			SAND pinky yellow, fine to medium grained, rounded to sub rounded quartz	
	50			with minor silcrete	
	55			with cream red brown clays and clay matrix	
	60			SAND medium grained sub rounded to sub angular quartz, orange red	
	65			fine grained, pinky yellow	
	70			medium grained reddy orange	
	75			SAND medium grained, sub angular to angular	
	80			and minor cream clay matrix, slightly finer grained, with fresh pyrite, cream & creamred	
	85			very hard, with blue grey feldspars,	
	90			BASEMENT	
	95				
	100				
	105				
	110				
	115				
	120				

SAMPLE Nos: 584746-584770

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

OTHER DETAILS

DRILLER: W.L. SIDES

DATE DRILLED: 1/6/80

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 448

ROTARY DRILL HOLE LOG

LOCATION: 25km. WNW Nunjikompita


AIR: FROM TO

RL COLLAR: T

CO-ORDS:

WATER: FROM 0 TO 60m

A.M.G: 16900E, 43800N. °

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
				SILTY SOIL cream
				nodular kunkar
	10			SILT light brown
				SILT/SAND cemented grey green and dark red
	20			SAND fine grained rounded quartz, reddish brown
				lense SILTY CLAY grey greenish
	30			SAND cemented grey greenish and dark red
				SAND fine grained rounded quartz
				grey brown
	40			SAND coarse grained sub rounded quartz, yellow staining
				SILTY CLAY orange red and yellow
	50			CLAY limonitic yellow
				BASEMENT sericitic schist red-white
				cream white with brassy brown tarnished pyr.
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 583441-583470

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 1/6/80

SCALE: 1 500

DRG./CODE No:

OTHER DETAILS

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 449


LOCATION: 24km WNW Nunjikompita

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM TO
WATER: FROM 0 TO 60m

RL COLLAR:
A.M.G 16900E, 4180QN

Geophysical Log Type: Geox	Depth Metres	Strip Log	Ox	Lithological Log	0017
	0			SILTY SOIL cream	
	5			SILT brown	
	10			SILT dark red	
	20			CLAYEY SILT brown-orange brown, yellowish minor creamy grey	
	30				
	40			SILTY CLAY white and orange brown minor SAND lenses fine to medium grained quartz	
	50			GRANITE minor coarse grained angular quartz in sericitic matrix	
	60				
	70				
	80				
	90				
	100				
	110				
	120				

SAMPLE Nos: 583471-583500

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000	LOGGED BY: G.HOOPER
DRILLER: W.L. SIDES	DATE DRILLED: 1/6/80
SCALE: 1 500	DRG./CODE No:

HOLE N° IR 450

RL COLLAR:

WATER: FROM...0.. TO..48m.....

A.M.G.:16900E,39800N...°

ORG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 452

ROTARY DRILL HOLE LOG

LOCATION: 21.5km WNW Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...Q... TO...60m.....

A.M.G: 1700E, 35900N.°

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log
				0020 CLAYEY SAND yellow brown, fine grained with calcrete
				CLAYEY SILT red brown
				SILCRETE cream yellow and red silcreted sands
	10	Sil		
				SAND yellow brown, fine grained, with silcreted sands
	20			SAND yellow brown, with minor cream and brown clays and clay matrix
				SAND fine grained, yellow brown, rounded quartz
	30			pinky red
				slightly coarser grained with minor cream clayey sand
	40			
	50			CLAY cream brown, brown and minor black
				CLAY white clay with quartz and felds
	60	+		weathered granite
		+		
		+		
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 584795-584824

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 1/6/80

OTHER DETAILS:

SCALE: 1 500


DRG./CODE No:

LOCATION: 17km WNW Nunjikompita ROTARY DRILL HOLE LOG

CO-ORDS: AIR: FROM..... TO.....
WATER: FROM 0 TO 102m.....

RL COLLAR:.....

A.M.G. 21300E, 34800N.....

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log	0021
				SILTY SOIL cream	
				SILT light brown	
	10				
				lense SILCRETE	
	20				
				CLAYEY SILT orange brown, minor grey white	
	30				
				SAND fine to medium grained, sub rounded quartz orange red	
	40				
				SAND medium to coarse grained, sub rounded to sub angular quartz, pink red	
	50			CLAY cream to light brown	
				SAND fine grained rounded quartz pink brown	
	60				
				SAND coarse grained sub angular quartz fairly clean minor traces of yellow oxidation	
	70				
				very minor CLAY black	
	80				
				SAND medium to coarse grained sub angular quartz trace pyrite	
	90			CLAY cream brown	
				CLAY black	
				CLAY grey brown	
				SAND medium grained sub rounded to sub angular quartz, much humic staining	
	100			GRANITE, white grey sericitic	
	110				
	120				

SAMPLE Nos: 584028-584078

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY G. HOOPER

DRILLER W.L. SIDES

DATE DRILLED 2/6/80

SCALE 1:500

DRG./CODE No:

OTHER DETAILS:

ROTARY DRILL HOLE LOG

LOCATION: 15.5km. WNW. Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0... TO...102m....

A.M.G. 23200E, 34500N

Geophysical Log Type: Geox	Depth Metres	Strip Log	Ox	Lithological Log	0022
				CLAYEY SAND yellow brown, with calcrete fine grained	
	10			SILTY CLAY yellow brown with silcrete red	
	20			CLAYEY SAND red brownly orange with minor interbedded cream silty clays	
	30				
	40			SAND reddy orange, fine grained, rounded quartz with minor clay (cream) very fine grained with minor clay matrix brown clayey silt	
	50			SILTY CLAY mucky pink red and yellow	
	60			SAND with minor clay matrix, red brown fine grained, slightly coarser fine to medium grained red brown fine grained fine to medium grained crimson	
	70			 pinkish grey fine to medium grained	
	80			 fine grained, pink	
	90			CLAY grey brown, with minor interbedded fine to medium grained sand SAND fine to medium grained, pinkish grey	
				CLAY grey brown, with minor fine to medium grained sands	
	100			CLAY white sticky clay with quartz weathered granite	
	110				
	120				

SAMPLE Nos: 584825-584875

REASON FOR HOLE:	DRILL TYPE MAYHEW 1000	LOGGED BY P. OWEN
OTHER DETAILS:	DRILLER W.L. SIDES	DATE DRILLED 1/6/80
	SCALE: 1 500	DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 13.5km WNW Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM... 0 ... TO... 108m

A.M.G: 24800E, 34200N..°

Geophysical Log Type: Geox	Depth Metres	Strip Log	Ox	Lithological Log
				CLAYEY SAND fine grained, yellow brown with calc
				SILTY CLAY red brown
				CLAYEY SAND with cream silcrete, red and red brown
	10			SAND fine grained, rounded quartz, pinky red with silcrete and minor silty clays orange
	20			CLAYEY SAND fine grained orange minor cream clayey silts
	30			
	40			SILTY CLAY yellow brown (mucky)
	50			SAND fine grained, reddly orange
	60			SAND medium grained, sub rounded to rounded quartz, yellow orange crimson red
	70			SAND coarse grained pinky grey, sub rounded to sub angular, mod. sort.
				SAND fine grained, micaceous, slightly finer grained, yellow brown fine to medium grained, with cream brown
	80			CLAY black brown, humic clay lense
				CLAY & SAND interbedded black brown clay and medium grained humic stained sub rounded to sub angular quartz, pyritic
	90			SAND medium grained, sub rounded to sub angular humic stained sand, pyrite
				CLAY black brown, brown and cream brown with minor sand as above
				SAND fine to medium grained, with minor inter bedded cream brown clays, mild humic staining pyritic, coarser towards base, sub rounded to sub angular quartz
	100			BASEMENT SAND quartz and felds and minor white clay weathered granite
	110			
	120			

SAMPLE Nos: 584876-584929

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY P. OWEN

DRILLER W.L. SIDES

DATE DRILLED 2/6/80

OTHER DETAILS:

SCALE 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 456

ROTARY DRILL HOLE LOG

LOCATION: 11.5km WNW Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....T.

CO-ORDS:.....

WATER: FROM.....O. TO...146m...

A.M.G.: 26700E, 33400N.°

Geophysical Log Type: Geoelect	Depth Metres	Strip Log	Ox	Lithological Log	0024
				KUNKAR & SILTY SOIL cream	
				SILT orange brown	
	10			SILT red brown	
				SILT/SAND grey white	
	20				
				SAND very fine grained rounded quartz cemented in places	
	30				
				CLAYEY SILT yellow-yellow brown and grey white	
	40				
				SAND/CLAYEY SAND fine grained rounded quartz red brown lenses of CLAYEY SILT grey white and yellow	
	60				
				SAND medium to coarse grained sub angular quartz much oxidation	
	80			SAND fine to medium grained sub rounded quartz pink brown lense CLAY brown black	
				CLAY black	
				SAND medium to coarse grained, sub rounded to sub angular quartz trace pyrite minor humic staining maybe slight suggestion of oxidised grains	
	90				
	100				
	110				
	120			GRAVEL very coarse grained	

SAMPLE Nos:

REASON FOR HOLE:

DRILL TYPE:

LOGGED BY:

OTHER DETAILS:

DRILLER:

DATE DRILLED:



SCALE: 1 500

DRG./CODE No:

CARPENTARIA EXPLORATION COMPANY PTY. LTD.
 ROTARY DRILL HOLE LOG

HOLE N^o IR 456

(Contd)

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log	0025
	130			GRAVEL very coarse grained, sub rounded quartz trace pyrite minor humic staining	
	140				
	150			GRANITE Hard	
	160				
	170				
	180				
	190				
	200				

SAMPLE Nos: 584079-584151

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW1000	LOGGED BY: G.HOOPER
DRILLER: W.L. SIDES	DATE DRILLED: 2/6/80
SCALE: 1:500	DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE NO IR 457

ROTARY DRILL HOLE LOG

LOCATION: 9.5km WNW Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM... 0... TO... 90m.....

A.M.G: 28700E, 32500N. °

Geophysical Log Type: Geopex	Depth Metres	Strip Log	Ox	Lithological Log	0026
				CLAYEY SAND fine grained, yellow brown with calc.	
				CLAYEY SILT red brown	
				SILCRETE cream blue green silcreted silt	
				CLAYEY SAND red brown, with silcreted silt	
	10				
				SAND fine grained, grey with silcreted sands	
				yellow	
				minor coarser fractions	
	20				
				SILTY CLAY cream yellow	
				yellow to yellow brown	
	30				
				SAND orange, fine grained rounded quartz	
	40			red	
				micaceous in parts	
	50				
				minor cream clays	
	60			and clayey matrix	
	70				
				slightly coarser, fine to medium grained	
				sub rounded quartz	
	80			SAND medium grained, sub rounded to sub angular	
				quartz, grey	
				CLAY & SAND interbedded black brown clay	
				and medium grained sub rounded to sub	
				angular quartz, humic stained, pyritic	
				and wood fragments	
	90			CLAY white clay with quartz and felds.	
				weathered granite	
	100				
	110				
	120				

SAMPLE Nos: 584930-584974

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY P. OWEN

DRILLER W.L. SIDES

DATE DRILLED 2/6/80

OTHER DETAILS:

SCALE 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 458

ROTARY DRILL HOLE LOG

LOCATION: 7km. WNW. Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0.. TO.. 14m.....

A.M.G: 30800E, 31700N.°

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log
				0027
				KUNKAR & SANDY SOIL
	10	SIL		SILT red brown
		+		SILCRETE
		+		GRANITE white kaolinitic clay and quartz
		+		Hard
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 584152-584158

REASON FOR HOLE:	DRILL TYPE MAYHEW 1000	LOGGED BY G.HOOPER
OTHER DETAILS:	DRILLER W.L. SIDES	DATE DRILLED 2/6/80
	SCALE 1 500	DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 459

ROTARY DRILL HOLE LOG

LOCATION: 5km WNW Nunjikompita

AIR: FROM 0 TO 12

RL COLLAR: 7

CO-ORDS:

WATER: FROM 12 TO 67m

A.M.G.: 32500E, 30900N. 9

Geophysical Log Type: Geopex	Depth Metres	Strip Log	Ox	Lithological Log
	0			SAND fine grained, pale brown
	5			CALCRETE
	10			CLAYEY SILT yellow to red brown
	20			
	30			
	40			
	50			CLAYEY SILT white, red brown and red
	55			CLAY black, less than 20cm thick
	60			GRITTY CLAY white fine grained granite
	70			
	80			
	90			
	100			
	110			
	120			

0028

SAMPLE Nos: 584975-585507

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000 LOGGED BY: P.BINKS

DRILLER: W.L. SIDES DATE DRILLED: 2/6/80

OTHER DETAILS:

SCALE: 1 500 DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 3.5km. WNW Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:TM

CO-ORDS:

WATER: FROM...0.. TO..96m.....

A.M.G: 34400E, 30800N. . °

Geophysical Log Type:		Depth Metres	Strip Log	Ox	Lithological Log	
Genex					CALCRETE & SAND fine grained, pale brown	0029
		10			CLAYEY SILT yellow brown	
		20				
		30			CLAYEY SILT red brown	
		40				
		50				
		60			SILTY CLAY off white to red brown	
		70			CLAY brown to grey	
					SAND fine grained, red brown	
					CLAY & SAND sand medium grained, sub angular	
		80			SAND medium to coarse grained, angular quartz grains, pale red brown	
					Drilled blind, no return	
		90			CLAY fragments of black brown clay in white clay matrix	
					CLAY weathered granite	
		100				
		110				
		120				

SAMPLE Nos: 584159-584206

REASON FOR HOLE:

OTHER DETAILS.

DRILL TYPE: MAYHEW 1000

DRILLER. W.L. SIDES

SCALE: 1 500

LOGGED BY: P. BINKS

DATE DRILLED. 2/6/80

DRG./CODE No:

LOCATION: 2km. NW. Nunjikompita

ROTARY DRILL HOLE LOG

AIR: FROM..... TO.....

RL COLLAR:.....T.

CO-ORDS:.....

WATER: FROM...0... TO...54m....

AMG: 35100E, 30800N.°

Geophysical Log Type: Georex	Depth Metres	Strip Log	Ox	Lithological Log
				0030.
				CALCRETE & SILTY CLAY pale brown
	10			SAND fine grained, well rounded, pale brown with fragments of silcrete
	20			SAND fine to medium grained, rounded quartz grains, pale brown to 38m.
	30			
	40			grey
	50			CLAY gritty, white and pink, weathered granite
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 585508-585534

REASON FOR HOLE:

OTHER DETAILS

DRILL TYPE: MAYHEW 1000

DRILLER: W.L. SIDES

SCALE: 1 500

LOGGED BY: P.BINKS

DATE DRILLED: 4/6/80

DRG/CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 1km NNE Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM 0 TO 72m

A.M.G: 37900E, 30500N



SAMPLE Nos: 584207-584242

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: G. HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 4/6/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 463

ROTARY DRILL HOLE LOG

LOCATION: 2.5km ENE Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...42m.....

A.M.G: 39800E, 30200N...°

Geophysical Log
Type: GeopexDepth
MetresStrip
Log

Ox

Lithological Log

0032

CALCRETE pale brown

SAND fine to medium grained, red brown

CLAYEY SAND sand, fine to medium grained,
sub rounded, red brown,
thin silcreted bandsSAND medium grained, sub rounded, red brown
slightly clayey

SAND coarse grained, angular quartz grains, purple

CLAY brown and yellow brown
gritty, weathered granite, white

SAMPLE Nos: 585435-585555

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. BINKS

DRILLER: W.L. SIDES

DATE DRILLED: 4/6/80

OTHER DETAILS:


SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 464

LOCATION: 4km ENE Nunjikompita ROTARY DRILL HOLE LOG

CO-ORDS: AIR: FROM.....TO..... RL COLLAR:.....
WATER: FROM 0 TO 48m A.M.G. 41700E, 29800N °

SAMPLE Nos: 584243-584266

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000 LOGGED BY: G. HOOPER

DRILLER: W.L. SIDES DATE DRILLED: 4/6/80

SCALE: 1:500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 5.5km E. Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM... Q... TO 54m.....

A.M.G.: 43200E, 29300N.°

Geophysical Log
Type: GeopexDepth
MetresStrip
Log

Ox

Lithological Log

0034

SAND fine grained, well rounded, brown
CLAYEY SAND with calcrete nodules, pale brown

SAND fine grained, well rounded quartz grains,
clayey
SILCRETED SAND grey
CLAYEY SAND with bands of silcrete

SAND fine to medium grained, well rounded
quartz grains, yellow brown

CLAYEY SAND fine to medium grained, well rounded
quartz grains, yellow brown.

SAND medium to coarse grained, angular quartz
grains, red brown, to purple brown
CLAY white, weathered granite

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000

DRILLER: W.L. SIDES

SCALE: 1 500

LOGGED BY: P. BINKS

DATE DRILLED: 4/6/80

DRG./CODE No:

SAMPLE Nos: 585556-585582

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 466

ROTARY DRILL HOLE LOG

LOCATION: 7.5km E Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....T.

CO-ORDS:.....

WATER: FROM 0 TO 54m

A.M.G: 45000E, 28800N. °

Geophysical Log Type: Georex	Depth Metres	Strip Log	Ox	Lithological Log	0035
	5	II		KUNKAR	
	10			SILT orange brown	
	20			CLAYEY SILT yellow brown to light brown minor cemented SILT bands	
	30			SILTY CLAY cream white, red purple yellow brown	
	40			CLAYEY SILT red purple to red brown SILTY CLAY cream white	
	50	+		GRANITE kaolinitic	
	60				
	70				
	80				
	90				
	100				
	110				
	120				

SAMPLE Nos: 584267-584293

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: G. HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 4/6/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 9.5km E. Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0... TO...48m.....

A.M.G: 46800E, 28000N.°



SAMPLE Nos: 585583-585606

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 4/6/80

OTHER DETAILS

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE NO IR 468

ROTARY DRILL HOLE LOG

LOCATION: 11.5km ESE Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0... TO...30m.....

A.M.G: 48700E, 27400N..0.

Geophysical Log
Type: GeoxDepth
MetresStrip
Log

Ox

Lithological Log

0037

CLAYEY SAND yellow brown with calcrete nodules
fine grained,
orange rounded

with silcreted sand

very fine grained clayey sand

CLAY red and white with quartz and felds
weathered granite

SAMPLE Nos: 585607-585621

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

OTHER DETAILS:

DRILLER: W.L. SIDES

DATE DRILLED: 4/6/80

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 13km ESE Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....T.

CO-ORDS:.....

WATER: FROM...0...TO...42m.....

A.M.G: 50700E, 27000N...°.

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log
				CLAYEY SAND yellow brown with calcrete, fine grain
				CLAYEY SAND orange brown, fine grained, rounded with minor clayey silt bands
	10			
	20			SAND fine grained, rounded, yellow with clay matrix
	30			CLAYEY SILT cream, yellow, cream, yellow and red SILTY CLAY varicoloured, brown red, cream, yellow SAND fine grained, yellow brown, with clay matrix
	40			CLAY cream yellow with quartz, weathered granite
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

0038

SAMPLE Nos: 585622-585642

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P. OWEN

OTHER DETAILS

DRILLER: W.L. SIDES

DATE DRILLED: 5/6/90

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 470

ROTARY DRILL HOLE LOG

LOCATION: 15km ESE Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM... 0... TO... 54m.....

A.M.G: 52200E, 27000N.°

Geophysical Log
Type: GeoexDepth
MetresStrip
Log

Ox

Lithological Log

0039

CLAYEY SAND with calcrete nodules, yellow brown
CLAYEY SAND orange brown, fine grainedCLAYEY SAND very fine grained, cream and yellow
cream with silcreted sand lensesSAND fine grained, rounded, cream yellow
with clay matrixSILTY CLAY cream blue green, brown with inter-
bedded white clay
CLAY brown, white and yellowCLAY & SAND interbedded yellow brown
fine grained sand with cream and brown
and green claysSANDY CLAY brown, yellow brown, fine grained
medium grained, sub rounded to sub angular
sand with interbed brown claysCLAY white, cream white with quartz, sericite
and felds
weathered granite

SAMPLE Nos: 585643-585669

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P.OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 5/6/80

OTHER DETAILS

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 471

LOCATION: 17km ESE Nunjikompita

ROTARY DRILL HOLE LOG

AIR: FROM TO

RL COLLAR: T.

CO-ORDS:

WATER: FROM ... 0 ... TO ... 72m ...

A.M.G: 54000E, 26300N .°.

Geophysical Log
Type: GeopexDepth
MetresStrip
Log

Ox

Lithological Log

0040

CLAYEY SAND yellow brown, fine grained, with calc.

CLAYEY SAND orange brown, fine grained rounded
orangeCLAYEY SAND cream white and yellow with
silcreted sand

CLAY cream grey

SAND & CLAY interbedded cream, red grey, clay
orange fine grained rounded sand

CLAY grey brown

SAND fine grained, orange, rounded
with minor cream claysCLAY multicoloured, red, grey, grey green
brown, white and blue white
with minor sandSAND & CLAY interbedded clay as above with
cream grey fine grained sand

SAND fine grained, yellow, pink red

CLAY & SAND interbedded fine grained, orange sand
and crimson, grey, blue green, red clays
with minor sandy clays

CLAY black brown, humic

with medium grained sub rounded to sub ang
humic stained quartz, and brown sandy
clays with wood fragmentsCLAY cream grey, with quartz and felds and
sericite, weathered granite

SAMPLE Nos: 585670-585705

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 5/6/80

OTHER DETAILS

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 472

ROTARY DRILL HOLE LOG

LOCATION: 19km ESE Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....m

CO-ORDS:.....

WATER: FROM...0...TO...66m.....

A.M.G.: 55900E, 25800N

Geophysical Log Type: Geox	Depth Metres	Strip Log	Ox	Lithological Log
	0			CLAYEY SAND yellow brown with calcrete, fine gr.
	5			CLAYEY SAND orange brown, very fine grained
	10			CLAY cream blue green
	15			CLAYEY SAND with cream silcreted sand, cream red brown
	20			SAND fine grained, rounded, orange brown, with clay matrix
	25			
	30			CLAYEY SAND fine grained cream white, yellow
	35			
	40			SAND fine grained, rounded, minor clay matrix orange to red brown
	45			
	50			SILTY CLAY cream brown
	55			CLAY black brown, humic
	60			CLAY cream clay with angular quartz and sericite weathered granite
	65			
	70			
	75			
	80			
	85			
	90			
	95			
	100			
	105			
	110			
	115			
	120			

0041

SAMPLE Nos: 585706-585738

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 6/6/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 21km. ESE Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...84m.....

A.M.G: 57800E, 25400N .°

Geophysical Log Type: Geopex	Depth Metres	Strip Log	Ox	Lithological Log	0042
				KUNKAR & SILTY SOIL cream	
				SILT brown to red brown	
	10			SILT/SAND cemented very fine grained quartz white to yellow	
	20			SAND fine-grained rounded quartz pale yellow	
	30			CLAYEY SILT cream	
	40			SAND fine to medium grained rounded quartz orange brown	
	50			lense SILT black, carbonaceous grey brown	
	60			SILTY CLAY cream brown	
	70			CLAY/SILTY CLAY black	
	80			lenses fine grained SAND with humic staining	
				CLAY black brown	
				SAND fine to medium grained, sub rounded to sub angular quartz, pyritic	
				GRANITE coarse grained quartz in micaceous brown Clay matrix	
	120				

SAMPLE Nos: 584294-584335

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 6/6/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA

CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 474

ROTARY DRILL HOLE LOG

LOCATION: 22.5km ESE Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM 0 TO 84m

A.M.G: 59600E, 24900N .°.

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log	0043
				SILTY SOIL	
				SAND cemented grey white	
	10			SILT cream yellow	
	20				
				SILT CLAYEY in part	
				yellow to red to orange	
	30			grey white	
	40			brownish	
	50			CLAY dark brown	
				lenses SAND fine grained rounded quartz, brown	
	60				
				CLAY brown black	
	70				
				SAND medium to coarse grained sub rounded to	
				sub angular quartz humic staining & pyrite	
	80			GRANITE	
	90				
	100				
	110				
	120				

SAMPLE Nos: 584336-584378

REASON FOR HOLE:	DRILL TYPE MAYHEW 1000	LOGGED BY G.HOOPER
	DRILLER W.L. SIDES	DATE DRILLED: 6/6/80
	SCALE: 1 500	DRG./CODE No:
OTHER DETAILS		

ROTARY DRILL HOLE LOG

LOCATION: 24.5km. ESE Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...Q...TO...96m.....

A.M.G: 61600E, 24500N..°

Geophysical Log Type: Geoelex	Depth Metres	Strip Log	Ox	Lithological Log
				0044
				CLAYEY SAND yellow brown, fine grained with calc.
				CLAYEY SAND orange brown fine grained
	10	Sil		SILCRETE AND SAND fine grained, yellow sand
		Sil		with cream, yellow silcreted sand
		Sil		
	20			SAND fine grained, rounded, yellow
	25			
	30			CLAYEY SAND red brown, fine grained
				with coarse grained sub angular quartz beds
	40			SAND fine grained, orange brown, with clay matrix
				very fine grained,
				orange
				with minor cream clays
	50			fine grained orange
				SANDY CLAY cream brown
	60			
				CLAY & SAND cream brown and black brown clay
				and interbedded gravelly sub rounded to
	70			sub angular quartz, humic stained, pyritic
				prominently more clay with minor coarse
				grained gravelly sands. (black brown)
	80			
				coarse grained, pyritic, mild humic stained
				quartz, and minor brown clay
	90	+		SAND with cream sandy clay with angular quartz
		+		and felds.
		+		weathered granite
		+		
		+		
	100			
	110			
	120			

SAMPLE Nos: 585739-585786

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W L. SIDES

DATE DRILLED: 6/6/80

OTHER DETAILS

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 26.5km ESE Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....T.....

CO-ORDS:.....

WATER: FROM... 0... TO... 60m.....

A.M.G: 63400E, 24200N...°

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NO LOG				KUNKAR & SANDY SOIL SILT orange brown SILCRETE & SAND cemented fine grained rounded quartz SILT, slightly CLAYEY yellow, grey white SAND fine grained rounded quartz, yellow brown and lenses SILT as above SAND fine grained rounded quartz, yellow brown samples to 54m drilled blind to 60m lost circulation HOLE ABD
				0045
				SAMPLE Nos: 584379-584405
REASON FOR HOLE:		DRILL TYPE MAYHEW 1000		LOGGED BY: G.HOOPER
OTHER DETAILS:		DRILLER: W.L. SIDES		DATE DRILLED 6/6/80
		SCALE 1 500		DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o: IR 476A

ROTARY DRILL HOLE LOG

LOCATION: 26.5km ESE Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....m

CO-ORDS:.....

WATER: FROM...0...TO...70m...

A.M.G.: 63400E, 24200N. °

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NO LOG				0046
				KUNKAR & SANDY SOIL
				SILT cream brown
				light brown
	10			
	20			
				SILCRETE & SAND cemented fine grained, rounded
				quartz
				SILT pale brown
	30			
				SAND very fine grained rounded quartz,
				yellow brown
	40			
				lenses CLAYEY SILT grey brown
	50			
				lenses CLAYEY SILT brown purple
				SAND as above, brown
	60			
				lense CARB SILT black
				GRAVEL very coarse grained, sub rounded quartz
				humic staining, slight suggestion of oxidn.
	70			LOST CIRCULATION
				HOLE ABD
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 584406-584444

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 6/6/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 476B

ROTARY DRILL HOLE LOG

LOCATION: 26.5km. ESE. Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...72m.....

A.M.G: 63400E, 24200N.°.



SAMPLE Nos: 584441-584476

REASON FOR HOLE 300mE 476
OTHER DETAILS 500mE 476A

DRILL TYPE: MAYHEW 1000

LOGGED BY: G. HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 7/6/80

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 28.5km. ESE. Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...42m.....

A.M.G: 65300E, 23700N...°

Geophysical Log
Type: GeoelectDepth
MetresStrip
Log

Ox

Lithological Log

CLAYEY SAND yellow brown with calcrete and topsoil

CLAYEY SAND orange brown fine grained

CLAYEY SAND & SILCRETE cream and red silcreted
sand and orange clay sand

with minor clays

CLAYEY SAND fine grained orange
with minor brown clayey silts
with minor red silty clays

SILTY CLAY red and cream browns

CLAYEY SAND fine grained orange brown
with minor silty claysCLAY cream and cream red clay with angular quartz
weathered granite

SAMPLE Nos: 585787-585807

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P. OWEN

OTHER DETAILS:

DRILLER: W.L. SIDES

DATE DRILLED: 6/6/80

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 478

ROTARY DRILL HOLE LOG

LOCATION: 17km. S. Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0... TO...52m.....

A.M.G: 34600E, 24300N. °

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log	0049
				CLAYEY SAND cream white, with calcrete with silcreted sand	
	10			SANDY CLAY cream white, yellow CLAYEY SAND orange brown with silcreted sand	
	20			SANDY CLAY orange brown (mucky) CLAYEY SAND orangy yellow fine grained	
	30				
	40			with nodular calcrete	
				with minor cream clay lenses	
				CLAY cream white cream brown and white	
	50			SAND medium grained angular quartz with cream red clay matrix weathered granite	
	60				
	70				
	80				
	90				
	100				
	110				
	120				

SAMPLE Nos: 585808-585833

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY P. OWEN

DRILLER W. L. SIDES

DATE DRILLED 7/6/80

SCALE 1 500

DRG./CODE No:

OTHER DETAILS:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 479

ROTARY DRILL HOLE LOG

LOCATION: 17km SSW Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...60m.....

A.M.G. 33100E (12700N) °

Geophysical Log
Type: GeoexDepth
MetresStrip
Log

Ox

Lithological Log

0050

KUNKAR, bouldery

SILT/SAND and SILCRETE boulders
yellow brownSAND/SILT very fine grained rounded quartz
yellow orangeSANDY CLAY cream white, medium to fine grained qtz
GRANITE coarse grained angular quartz
purplish and cream white
minor pink felds
in sericitic, kaolinitic clay

SAMPLE Nos: 584477-584506

REASON FOR HOLE:

HOLE 2M W 14m ABD

OTHER DETAILS

DRILL TYPE: MAYHEW 1000

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 7/6/80

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 480

ROTARY DRILL HOLE LOG

LOCATION: 18km SSW Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...48m.....

A.M.G. 13000E 11200N

Geophysical Log Type: Geoelect	Depth Metres	Strip Log	Ox	Lithological Log
				CLAYEY SAND fine grained, cream white with calcrete top 2m
	10			
	20			CLAYEY SAND very fine grained rounded quartz yellow brown with silcreted sand
	30			orange very fine grained
	40			red
	45			slightly coarser grained
	50			CLAY red white and mauve with sericite weathered granite
	60			
	70			
	80			
	90			
	100			
	110			
	120			

0051

SAMPLE Nos: 585858-585881

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000	LOGGED BY P. OWEN
DRILLER W.L. SIDES	DATE DRILLED 7/6/80
SCALE 1 500	DRG./CODE No:

OTHER DETAILS

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 481

ROTARY DRILL HOLE LOG

LOCATION: 18km. SW. Nunjikompita


AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM 0 TO 48m

A.M.G: 29100E, 13400N. °

Geophysical Log Type: Geox	Depth Metres	Strip Log	Ox	Lithological Log	0052
	0			CLAYEY SAND cream white, fine grained with calc. with silcreted sand	
	10			CLAYEY SAND orange brown, fine grained with cream lenses	
	20			CLAYEY SAND fine grained, rounded quartz, in clay matrix with sandy clays, cream orange with silcreted sands	
	30			CLAYEY SILT/SAND very fine grained, orange, cream and red lenses	
	40			with medium to coarse grained, sub angular to sub rounded quartz CLAY cream pink with sericite weathered granite	
	50				
	60				
	70				
	80				
	90				
	100				
	110				
	120				

SAMPLE Nos: 585834-585857

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000 LOGGED BY: P. OWEN

DRILLER: W.L. SIDES DATE DRILLED: 7/6/80

OTHER DETAILS

SCALE 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 482

ROTARY DRILL HOLE LOG

LOCATION: 18.5km SW Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....T.

CO-ORDS:.....

WATER: FROM...Q...TO...48m.....

A.M.G: 27300E, 13800N. °.

Geophysical Log
Type: GeoeexDepth
MetresStrip
Log

Ox

Lithological Log

0053

CALCRETE fragmented calcrete, cream white

CLAYEY SAND orange brown, very fine to fine grained
cream lense
with silcreted sand (orange)SILTY CLAY very fine grained silty clay, mauve,
yellow and cream brownCLAYEY SAND orange, fine grained,
with minor silcretes
and silty and sandy clays

red

CLAY white clay with angular quartz and felds
and sericite, weathered granite

SAMPLE Nos: 585882-585905

REASON FOR HOLE:

DRILL TYPE MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 8/6/80

OTHER DETAILS:

SCALE 1 500

DRG/CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 19km. SW. Nunjikompita


AIR: FROM TO

RL COLLAR: 7

CO-ORDS:

WATER: FROM ... 0 ... TO ... 60m

A.M.G.: 25800E, 14800N. °

Geophysical Log Tone. Geoelect	Depth Metres	Strip Log	Ox	Lithological Log
	0		/	KUNKAR/LIMESTONE
	5		/	SAND/SILT CALCAREOUS cream
	10		/	CLAY cream brown
	15		/	CLAYEY SILT greenish, hard, compact
	20		/	CLAYEY SILT yellow orange
	25		/	SILT/SAND very fine grained rounded quartz,
	30		/	red
	35		/	SAND medium grained sub rounded quartz
	40		/	pink red, yellow orange
	45		/	GRANITE grey white sericitic
	50		/	coarse grained angular quartz
	55		/	
	60		/	
	65		/	
	70		/	
	75		/	
	80		/	
	85		/	
	90		/	
	95		/	
	100		/	
	105		/	
	110		/	
	115		/	
	120		/	

0054

SAMPLE Nos: 585007-585036

REASON FOR HOLE:

DRILL TYPE: MAYHEW 100 LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 8/6/80

SCALE: 1 500

DRG./CODE No:

OTHER DETAILS

ROTARY DRILL HOLE LOG

LOCATION: 19km. SW. Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....m.

CO-ORDS:.....

WATER: FROM...0... TO...48m.....

A.M.G.: 24200E, 15900N.°.

Geophysical Log
Type: GeorexDepth
MetresStrip
Log

Ox

Lithological Log

0055

CALCRETE fragmented calcrete
cream whiteCLAYEY SAND/SILT orange brown, very fine to
fine grained, with silcreted sandwith minor mauve clays and cream silty clays
very fine grained (clayey silt)

red

CLAYEY SAND fine to medium grained, red sub
rounded to sub angularCLAY cream white and red with sericite
weathered basement

SAMPLE Nos: 585906-585929

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

OTHER DETAILS:

DRILLER: W.L. SIDES

DATE DRILLED: 8/6/80

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPTA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 485

LOCATION: 19.5 km. SW. Nunjikompita

ROTARY DRILL HOLE LOG

AIR: FROM.....TO.....

RL COLLAR:.....7.

CO-ORDS:.....

WATER: FROM...0...TO...96m.....

A.M.G: 22700E, 17100N. °

Geophysical Log
Type: Geoex

Depth
Metres

Strip
Log

Ox

Lithological Log

0056

KUNKAR

SILT/SAND calcareous, cream white

SILT slightly CLAYEY
orange brown

CLAY grey purple

CLAYEY SILT light brown grey white

red brown, yellow orange and light brown

SANDY CLAY yellowish, fine to medium grained
sub rounded quartz

CLAY brown black slightly SILTY
lense SAND fine grained, rounded quartz
yellow brown

SAND medium grained sub rounded to sub angular
quartz, humic staining

GRANITE minor coarse grained angular quartz
in micaceous sericitic matrix

SAMPLE Nos: 585037-585085

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE MAYHEW 1000

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 8/6/80

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 19.5km SW Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM 0... TO 7.8m...

A.M.G. 21500E, 18400N

Geophysical Log Type: Geoex.	Depth Metres	Strip Log	Ox	Lithological Log
				0057
				CALCRETE fractured calcrete and calcified sands, cream white
	10			
				CLAYEY SAND/SILT orange brown, with silcreted sand/silt very fine grained
	20			
				with mauve clays
	30			
				red brown, with silcrete frags. fine grained
	40			
	50			SAND red brown, with clay matrix, medium grained rounded to sub rounded quartz and sil.frags
				CLAY & SAND cream brown clay and oxidised sand as above
	60			CLAY & SAND cream brown, brown & black, some micaceous clay with medium grained sub round humic pyritic quartz
				CLAY, black brown humic
	70			SAND medium grained sub rounded, humic stained pyritic with cream clays
				CLAY cream white clay with angular quartz clays and sericite weathered granite
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 585930-585968

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P.OWEN

DRILLER: W.L. SIDES

DATE DRILLED 8/6/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 19.5km WSW Nunjikompita


AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM 0 TO 54m

A.M.G: 2060QE, 2020DN. °.

Geophysical Log Type: Geon	Depth Metres	Strip Log	Ox	Lithological Log	0058
	5			KUNKAR	
	10			SILT calcareous, cream	
	15			CLAYEY SILT brown and grey green hard compact	
	20			CLAY calcareous cream	
	25			SILCRETE	
	30			CLAY & SAND grey purple clay, very fine grained rounded quartz, yellow-brown green	
	35			SAND very fine grained rounded quartz, yellow-brown green	
	40			SAND fine to medium grained sub rounded quartz yellow green	
	45			SAND medium to coarse grained sub angular qtz. red	
	50			GRANITE much coarse grained angular quartz in white kaolinitic matrix	
	55				
	60				
	65				
	70				
	75				
	80				
	85				
	90				
	95				
	100				
	105				
	110				
	115				
	120				

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000

DRILLER: W.L. SIDES:

SCALE: 1 500

LOGGED BY: G.HOOPER

DATE DRILLED: 8/6/80

DRG./CODE No:

SAMPLE Nos: 585086-585112

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 488

ROTARY DRILL HOLE LOG

LOCATION: 18.5 km WSW Nunjikompita

AIR: FROM..... TO.....

RL COLLAR:.....m

CO-ORDS:.....

WATER: FROM 0 TO 48m

A.M.G. 20300E, 22200N

Geophysical Log
Time. Geoex.Depth
MetresStrip
Log

Ox

Lithological Log

0059

CALCRETE calcrete particules and calcified
fine grained sand

CLAYEY SAND orange brown, fine grained rounded

CLAYEY SAND reddy orange fine grained (mucky)

with mauve clay lenses

CLAYEY SILT orange brown, with grey clays

CLAYEY SAND fine grained, red, with silcreted
and ferricreted particles.SILTY CLAY yellow, micaceous, fine silty clay
CLAY cream white and red clay with angular
quartz and sericite
weathered granite

SAMPLE Nos: 585969-585992

REASON FOR HOLE:

OTHER DETAILS

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: W.L. SIDES

DATE DRILLED: 9/6/80

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE NO IR 489

ROTARY DRILL HOLE LOG

LOCATION: 18.5km WSW Nunjikompita

AIR: FROM TO


RL COLLAR: T

CO-ORDS:

WATER: FROM 0 TO 72m

A.M.G: 19900E, 23900N

0060

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
	0			KUNKAR & SILT calcareous
	10			SILT light brown
				brown
				minor grey white
	20			SILTY CLAY dark brown and yellow and pink grey
				SILTY SAND yellow brown, fine grained rounded quartz
	30			
				SAND fine grained, rounded quartz
	40			orange brown
				red brown
	50			SAND medium grained sub rounded to sub angular quartz, pink red and yellow orange
				CLAY brown micaceous
				lenses SAND fine grained rounded quartz
	60			brown
				CLAY black
				GRANITE coarse grained angular quartz in white CLAY matrix
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 585113-585148

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE MAYHEW 1000	LOGGED BY G.HOOPER
DRILLER W.L. SIDES	DATE DRILLED 8/6/80
SCALE 1 500	DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 490

ROTARY DRILL HOLE LOG

LOCATION: 19km WSW Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...90m...

A.M.G: 18900E, 25700N

Geophysical Log Type:	Log Geoex	Depth Metres	Strip Log	Ox	Lithological Log	0061
					KUNKAR & SILT calcareous cream	
		10				
					SILT pale brown	
		20			SILCRETE	
					SILT/SAND very fine grained rounded quartz pale brown	
		30				
					SILCRETE	
					SAND fine grained rounded quartz, light brown	
		40				
					pink brown	
		50				
					SAND medium to coarse grained sub rounded quartz yellow orange	
		60			CLAY grey brown	
					CLAY black and woody	
		70				
					SAND fine grained rounded to sub rounded quartz clean	
		80				
					SAND medium to coarse grained sub rounded to sub angular quartz, trace pyrite trace oxidation yellow orange staining	
					SILTY CLAY brown black	
					SAND fine to medium grained rounded quartz trace pyrite, medium to coarse towards base	
		90			GRANITE much coarse grained angular quartz in white kaol. matrix	
		100				
		110				
		120				

SAMPLE Nos: 585149-585193

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: G.HOOPER

OTHER DETAILS

DRILLER: W.L. SIDES

DATE DRILLED: 9/6/80

SCALE: 1 500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 491


LOCATION: 20.5km WSW Nunjikompita

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM.....TO.....
WATER: FROM...0...TO...150m...

RL COLLAR:.....
A.M.G. 17200E, 27000N °

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log	0062
	5	++		KUNKAR	
	10	++		SILT calcareous, cream	
	20			SILT white and light brown	
	25	SIL		SILCRETE	
	28			CLAYEY SILT yellow brown and orange	
	30				
	40				
	50				
	60			SAND slightly CLAYEY medium grained sub rounded quartz, yellow and red brown	
	65			CLAY grey brown	
	70			SAND medium grained sub rounded quartz, much oxidation	
	80			CLAY black	
	85			SAND fine to coarse grained sub rounded quartz	
	90			SAND medium to coarse grained sub rounded to sub angular quartz minor yellow staining.	
	95			lenses CLAY, black and SILTY	
	100			lense CLAY black, mild humic staining	
	105			SAND fine grained rounded quartz, oxidised?	
	110			SAND fine to medium grained, humic staining	
	115			CLAY dark brown	
	120			SAND fine to medium grained, sub rounded quartz trace pyrite, mild humic staining	
				coarse grained sub rounded quartz	
				GRAVELLY SAND mild h.	

SAMPLE Nos: 585194-585268

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE:

DRILLER:

SCALE

1 500

LOGGED BY:



DATE DRILLED:

DRG./CODE No:

ROTARY DRILL HOLE LOG

Cont

0000

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
	130			GRAVELLY SAND very coarse grained, sub rounded quartz, clean, mild humic staining
				SAND medium to coarse grained, sub rounded to sub angular quartz.
	140			GRAVELLY SAND very coarse grained, sub rounded quartz, clean, mild humic staining trace pyrite
	150			CLAY white, weathered granite
	160			
	170			
	180			
	190			
	200			

SAMPLE Nos: 585194-585268

REASON FOR HOLE:

DRILL TYPE: MAYHEW 100

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 9/6/80

OTHER DETAILS:

SCALE: 1:500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 492

ROTARY DRILL HOLE LOG

LOCATION: 22km W Nunjikompita

AIR: FROM.....TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0...TO...102m...

A.M.G: 15700E, 27800N

Geophysical Log
Type: GeoexDepth
MetresStrip
Log

Ox

Lithological Log

0064

KUNKAR & SILT calcareous

SILT light brown

SAND & SILTY CLAY fine grained rounded quartz
cream and light brown

SILTY CLAY yellow brown, light brown

SILT/SAND very fine grained rounded quartz
red brown

SAND fine grained rounded quartz, red brown

fine to medium grained rounded quartz

CLAY black and woody

CLAY black and woody

lense SAND medium grained sub rounded quartz
may be reduced or oxidisedSAND medium grained sub rounded quartz,
brown colour, trace pyrite, but appears
to be oxidised (yellow staining)
lenses CLAY black

CLAY dark brown

SAND medium grained sub rounded to sub angular
quartz with humic stainingGRANITE coarse grained angular quartz
in clay matrix

SAMPLE Nos: 585269-585319

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000

LOGGED BY: G.HOOPER

DRILLER: W.L. SIDES

DATE DRILLED: 9/6/80

SCALE: 1:500

DRG./CODE No:


LOCATION: 23.5km W. Nunjikompita

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM.....TO.....
WATER: FROM 0...TO...72m...

RL COLLAR:.....
A.M.G: 13800E, 28700N.

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log	0065
	5	+		CALCRETE	fractured calcrete and calcreted sand
	10	+			
	15	+		CLAYEY SAND	orange brown, fine grained
	20	+			orangy yellow, micaceous
	25	+			red brown, orange and cream, with minor medium to coarse grained quartz, sub rounded to sub angular
	30	+			
	35	+		CLAYEY SAND	medium grained orange, sub rounded to sub angular poorly sorted
	40	+			
	45	+		CLAY & SAND	cream brown micaceous clay interbedded with a poorly sorted medium grained sub rounded to sub angular sand, some orange clay, and gravelly qtz some fine grained lenses, more sand than clay.
	50	+			
	55	+		CLAY	cream pink, with quartz and felds, and sericite cream grey, weathered granite
	60	+			
	65	+			
	70	+			
	75	+			
	80				
	85				
	90				
	95				
	100				
	105				
	110				
	115				
	120				
	125				

586507-586528

SAMPLE Nos: 585993-586006

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000 LOGGED BY: P.OWEN
DRILLER: W.L. SIDES DATE DRILLED: 10/6/80
SCALE: 1 500 DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 25km. W. Nunjikompita







AIR: FROM..... TO.....

RL COLLAR:.....

CO-ORDS:.....

WATER: FROM...0... TO...84m....

A.M.G: 12600E, 30000N..°

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log	0066
				KUNKAR	
				SILT light brown	
	10			SILCRETE	
				SILT grey white dark red and light brown cemented in parts	
	20			SILT yellow brown slightly CLAYEY	
	30				
	40			SILT/SAND very fine grained rounded quartz slightly CLAYEY pale red brown	
	50				
	60			SAND slightly CLAYEY medium grained, sub rounded quartz, pale red brown	
	70			SILTY CLAY black minor dark brown interbedded SAND fine to medium grained sub rounded quartz, yellow staining	
	80			CLAY white, weathered granite	
	90				
	100				
	110				
	120				

SAMPLE Nos: 585320-585361

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: G. HOOPER


OTHER DETAILS:

DRILLER: W. L. SIDES

DATE DRILLED: 10/6/80

SCALE: 1 500

DRG./CODE No:

Geophysical Log Type: Geoex	Depth Metres	Strip Log	Ox	Lithological Log
				0067
				CALCRETE cream white, fractured calcrete and calcareous sand
				CLAYEY SAND orange brown, fine grained
				SILCRETE silcreted sand orange and red
				SAND yellow brown, medium grained sub- rounded to sub angular quartz with silcrete frags.
	10			
	20			
	30			
	40			
	50			
	60			CLAY & SAND cream brown, micaceous clay and medium grained sub rounded to sub angular quartz
				CLAY black brown
				sand
	70			CLAY cream white, with angular quartz and sericite weathered granite
	80			
	90			
	100			
	110			
	120			

PROSPECT: NUNJIKOMPITIA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 800

LOCATION: 19.5km E Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM 0 TO 20m
WATER: FROM 0 TO 20mRL COLLAR: 122
A.M.G.: 74300E, 09900NGeophysical Log
Type:Depth
MetresStrip
Log

Ox

Lithological Log

0068

NOT LOGGED

10

20

30

40

50

60

70

80

90

100

110

120

CLAYEY SAND orange, fine grained with calcrete

SILCRETE yellow coarse grained silcreted sand

GRANITE cream clay with feldspar and angular quartz

SAMPLE Nos: 593007-593015

REASON FOR HOLE:

DRILL TYPE: MAYHEW 100 LOGGED BY: P. OWEN

OTHER DETAILS:

DRILLER: THOMPSON DRILL DATE DRILLED: 9/10/80

SCALE: 1:500

DRG./CODE No:

PROSPECT: NUNJIKOMPITA

CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 801

LOCATION: 20km E Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM: TO: 24m

RL COLLAR: 124

WATER: FROM: 0 TO:

A.M.G: 75800E, 11300N

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NOT LOGGED				CLAYEY SAND fine grained, calcareous, orange
	10	SIL		SILCRETE coarse grained silcreted sand, orange
	20			GRANITE cream clay with sericite and angular quartz
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 593016-593027

REASON FOR HOLE:

OTHER DETAILS

DRILL TYPE: MAYHEW 1000

DRILLER: THOMPSONS

SCALE: 1 500

LOGGED BY: P.OWEN

DATE DRILLED: 9/10/80

DRG./CODE No:

PROSPECT: NUNJIKOMPITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N° IR 802

LOCATION: 21km E Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM.....TO.....
WATER: FROM 0 TO 24m

RL COLLAR: 100 m

AM G 77600E, 12300N o

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NOT LOGGED				0070 CLAYEY SAND fine grained, orange, calcareous with calcrete and silcreted sand
	10			GRANITE cream clay, with sericite fresh granite with feldspar biotite and angular quartz
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 593028-593039

REASON FOR HOLE:

DRILL TYPE: MAYHEW 100

LOGGED BY: P. OWEN

DRILLER: THOMPSONS

DATE DRILLED: 9/10/80

OTHER DETAILS:

SCALE: 1:500

DRG./CODE No:

PROSPECT: NUNJIKOMPTIA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 803

LOCATION: 22km E Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM 0 TO 8

RL COLLAR: ...100...m

WATER: FROM 8 TO 22m

A.M.G: 79800E, 12700N .°

Geophysical Log
Type:Depth
MetresStrip
Log

Ox

Lithological Log

0071

NOT LOGGED

SAND fine grained, yellow with calcrete at top

CLAY black grey

BASEMENT chips of "granitic" basement
very hard

SAMPLE Nos: 593039-593050

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: THOMPSONS

DATE DRILLED: 9/10/80

OTHER DETAILS:

SCALE: 1:500

DRG/CODE No:

PROSPECT: NUNJIKOMRITA CARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE NO IR 804

LOCATION: 18km E Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM.....TO.....
WATER: FROM 0 TO 18m

RL COLLAR: 110
A.M.G: 72700E, 08800N

Geophysical Log Type:	Depth Metres	Strip Log	Ox	Lithological Log
NOT LOGGED				0072
				CLAYEY SAND fine grained, orange, with calcrete
				GRANITE red sand, medium to coarse grained, sub angular to angular cream clay with sericite
	10			
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			
	110			
	120			

SAMPLE Nos: 593051-593059

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE: MAYHEW 1000	LOGGED BY: P.OWEN
DRILLER: THOMPSONS	DATE DRILLED: 9/10/80
SCALE: 1:500	DRG./CODE No:

ROTARY DRILL HOLE LOG

LOCATION: 2km E Wirrulla

CO-ORDS:

AIR: FROM.....TO.....

RL COLLAR: ...88.....T.

WATER: FROM 0.....TO 42m.....

AMG: 58800E, 14700N. °

Geophysical Log
Type:Depth
MetresStrip
Log

Ox

Lithological Log

0073

NOT LOGGED

CALCAREOUS SAND powdered calcrete

SILTY/SANDY CLAY orange

SILCRETE silcreted fine grained sand, cream,
with fine grains, with fine grained yellow
sandSAND fine grained, yellow, orange
and red

GRANITE angular quartz and feldspar with biotite

SAMPLE Nos: 593060-593080

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: THOMPSONS

DATE DRILLED: 9/10/80

OTHER DETAILS:

SCALE: 1:500

DRG./CODE No:

PROSPECT: NUNJIKOMPITACARPENTARIA EXPLORATION COMPANY PTY. LTD.

HOLE N^o IR 806

LOCATION: 4km E Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM 0 TO 30m
WATER: FROM 0 TO 30m

RL COLLAR: 90
A.M.G. 60200E, 14800N

Geophysical Log
Type:

Depth
Metres

Strip
Log

Ox

Lithological Log

0074

NOT LOGGED

CLAYEY SAND fine grained, orange with calcrete
and silcreted sand and calcareous sand

SAND fine grained, yellow and orange
with minor silcrete

GRANITE white feldspar and angular quartz

SAMPLE Nos: 593021-593095

REASON FOR HOLE:

DRILL TYPE: MAYHEW 1000

LOGGED BY: P. OWEN

DRILLER: THOMPSONS

DATE DRILLED: 9/10/80

OTHER DETAILS:

SCALE: 1 500

DRG./CODE No:

LOCATION 6km E. Wirrulla

ROTARY DRILL HOLE LOG

CO-ORDS:

AIR: FROM.....TO.....
WATER: FROM 0.....TO 24m.....RL COLLAR: .92.....m
A.M.G 62200E, 15000N.....oGeophysical Log
Type:Depth
MetresStrip
Log

Ox

Lithological Log

0075

CLAYEY SAND yellow brown with topsoil
SILCRETE & CLAYEY SAND cream silcreted
sand with fine grained orange
clayey sandGRANITE highly weathered, with red & yellow
sericitic clay

10

20

30

40

50

60

70

80

90

100

110

120

SAMPLE Nos: 593096-593107

REASON FOR HOLE:

OTHER DETAILS:

DRILL TYPE MAYHEW 1000


DRILLER THOMPSONS

SCALE 1:500

LOGGED BY P. OWEN

DATE DRILLED: 9/10/80

DRG./CODE No:






LEGEND


- 15 ROTARY DRILL HOLE WITH THICKNESS (in metres) OF EOCENE SEDIMENTS
- 40 — CONTOURS OF THICKNESS (in metres) OF EOCENE SEDIMENTS
- 20 —

SCALE 1:100,000
0 2 4 6 8 10
KILOMETRES

REVISION	SCALE 1:100,000	CARPENTARIA EXPLORATION COMPANY PTY. LTD.
1	GEO. G.H., P.O., P.B.	E.L. 632 NUNJIKOMPITA
2	DRAWN J.M.	(NARLABY CHANNEL PROJECT)
3	CHECKED J.M.	SOUTH AUSTRALIA
4	DATE AUG. 1980	3882-1
5	MICROFILMED	ISOPACH MAP
6	ROLL UP	OF EOCENE SEDIMENTS
7	MINING FIELD OR DISTRICT NARLABY CHANNEL, STH. AUST.	DRAWN 15772




REVISION		SCALE 1:100,000	CARPENTARIA EXPLORATION COMPANY PTY. LTD.
NOV.1980	G.M.	GEO. G.H., P.O., P.B.	E.L. 632 'NUNJIKOMPITA' NARLABY CHANNEL PROJECT DRILL HOLE LOCATIONS
		DRAFT J.M.G.	
		CHECKED	
		DATE JULY, 1980	
		MICROFILMED	
		ROLL NO.	
MINING FIELD OR DISTRICT			3882-3
			DRG. NO. 15770




LEGEND

- 55 ROTARY DRILL WITH THICKNESS (in metres) OF POST-EOCENE SEDIMENTS
- 20 — CONTOURS OF THICKNESS (in metres) OF POST-EOCENE SEDIMENTS
- 40 —



CARPENTARIA EXPLORATION COMPANY PTY LTD	
G.H., P.O., P.B.	E.L. 632 NUNJIKOMPITA
JMc	(NARLABY CHANNEL PROJECT)
178	SOUTH AUSTRALIA
AUG 1980	3882-4
ISOPACH MAP of	
POST-EOCENE SEDIMENTS	
NARLABY CHANNEL : STH. AUST. : 15773	




LEGEND

- +40
- +20 —
- 0 —
- -20 —

ROTARY DRILL HOLE WITH HEIGHT (in metres) OF PRE-EOCENE BASEMENT ABOVE SEA-LEVEL

CONTOURS OF HEIGHT (in metres) OF PRE-EOCENE BASEMENT RELATIVE TO SEA LEVEL



REVISION		SCALE 1:100,000	CARPENTARIA EXPLORATION COMPANY PTY LTD
OCT 1980	P.O.	GEO G.H., P.O., P.B.	E.L.632 NUNJIKOMPITA (NARLABY CHANNEL PROJECT) SOUTH AUSTRALIA
NOV.1982	GH	DRAFT INTO DRAFTING	
		CHECKED:	
		DATE AUG 1980	PRE - EOCENE BASEMENT CONTOURS
		MICROFILMED	
		ROLL N°	
MINING FIELD OR DISTRICT: NARLABY CHANNEL : STH. AUST			ORG N° 15861

3882-5

LOGGING DATA


DATE 2-6-80

LOCATION		GAMMA RAY	
STATE	SA	FIRST READING	145.0M
REGION	NUNTIKOMPITA	RANGE	40CPD
PROJECT		TIME CONSTANT	2SEC
HOLE DATA		LOGGING SPEED	7M/MIN
HOLE N°	TR 456	PAPER SCALE	100:1
HOLE SIZE	434	BACKGROUND COUNTS	60CPD
CASING		DETECTOR SIZE	1" x 3/4", 2 1/2 x 7/8"
T.D.	147.3M	DIGITAL READ OUT	✓
SURFACE ELEVATION			
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	49.8M	FIRST READING	144.3M
DRILLER		RESIST. SCALE (M/DIV.)	3
INTERPRETATION DATA		S.P. SCALE (M/DIV.)	2
PROBE N°	C1	PROBE SIZE	1 5/8"
CALIBRATION STANDARD		RES. TYPE	SINGLE POINT
'K' FACTOR		RIG TIME	
DEAD TIME	7µSEC		
OPERATOR	W.MCG.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 1-6-80

LOCATION		GAMMA RAY	
STATE	SA		
REGION	NUNSIKOMPITA	FIRST READING 56.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N°	IR 452	LOGGING SPEED 7M/MIN	
HOLE SIZE	4 3/4"	PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 56.0M	
T.D.	59.0M	DETECTOR SIZE 1" x 3/4", 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	32.0M	FIRST READING 55.6M	
DRILLER		RESIST. SCALE (M/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE N°	C.1	PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME	7 μSEC		
OPERATOR	W. MFG.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA

DATE 2.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 106.0M	
REGION NUNTIKOMPITA		RANGE 40 CPS	
PROJECT		TIME CONSTANT 2 SEC	
HOLE DATA		LOGGING SPEED 7 M/MIN	
HOLE NO. IR 453		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 20 CPS	
CASING		DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 1/8"	
T.D. 109.2M		DIGITAL READ OUT ✓	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MUD+WATER		FIRST READING 105.6M	
FLUID LEVEL 39.7M		RESIST. SCALE (Ω/DIV.) 5	
DRILLER		S.P. SCALE (MV/DIV.) 3	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE NO. C.1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 μSEC			
OPERATOR W. MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY


DATE 2.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NUNTIKOMPITA	FIRST READING 63.0M
PROJECT	RANGE 40 CPD
HOLE DATA	TIME CONSTANT 2 SEC
HOLE N° IR 459	LOGGING SPEED 7 M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 60 CPS
T.D. 66.0M	DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD+WATER	ELECTRIC
FLUID LEVEL 3.0M	FIRST READING 62.6m
DRILLER	RESIST. SCALE (~ / DIV.) 4
INTERPRETATION DATA	S.P. SCALE (MY / DIV.) 3
PROBE N° C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 μSEC	
OPERATOR W.M.C.G.	
REMARKS	



S P

RESISTIVITY



LOGGING DATA


DATE 1-6-80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 57.0M	
REGION NUNTIKOMPITA		RANGE 40 CPD	
PROJECT		TIME CONSTANT 2 SEC	
HOLE DATA		LOGGING SPEED 7 M/MIN	
HOLE N° IR 449		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 170 CPS	
CASING		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
T.D. 59.9M		DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MUD + WATER		FIRST READING 56.6M	
FLUID LEVEL 11.3M		RESIST. SCALE (Ω/DIV.) 5	
DRILLER		S.P. SCALE (MV/DIV.) 3	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 μSEC			
OPERATOR W.McG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA

DATE 2.6.80


LOCATION		GAMMA RAY	
STATE SA			
REGION NUNSIKOMPITA		FIRST READING 88.0M	
PROJECT		RANGE 40 CPS	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N° TR 455		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 20 CPS	
T.D. 90.1M		DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT ✓	
BOREHOLE MEDIUM MUD + WATER		ELECTRIC	
FLUID LEVEL 7.2M		FIRST READING 87.6M	
DRILLER		RESIST. SCALE (K/DIV.) 3	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 2	
PROBE N° C1		PROBE SIZE 1 9/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 µSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

455



LOGGING DATA


DATE 1.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNTIKOMPITA		FIRST READING 52.0M	
PROJECT		RANGE 40 CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N° IR 451		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100'	
CASING		BACKGROUND COUNTS 80 CPS	
T.D. 54.3M		DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 4.1M		FIRST READING 51.6M	
DRILLER		RESIST. SCALE (Ω/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W.M.G.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 1-6-80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNTIKOMPITA		FIRST READING 58.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N° TR 448		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 120 CPS	
T.D. 60.1M		DETECTOR SIZE 1" x 3/4", 2 1/2" x 1/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD + WATER		ELECTRIC	
FLUID LEVEL 8.6M		FIRST READING 57.6M	
DRILLER		RESIST. SCALE (M/DIV.) 5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W. MCG			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 1.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNSIKOMPITA		FIRST READING 101.0M	
PROJECT		RANGE 40 CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N° IR 454		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 80 CPS	
T.D. 103.4M		DETECTOR SIZE 1" x 3/4" x 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 28.0M		FIRST READING 100.6M	
DRILLER		RESIST. SCALE (M/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 MSEC			
OPERATOR W.M.G.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 9.6.80

LOCATION		GAMMA RAY	
STATE	SA	FIRST READING	87.0M
REGION	NUNSIKOMPITA	RANGE	40CPD
PROJECT		TIME CONSTANT	2SEC
HOLE DATA		LOGGING SPEED	7M/MIN
HOLE N°	IR 490	PAPER SCALE	100:1
HOLE SIZE	4 3/4"	BACKGROUND COUNTS	70CPS
CASING		DETECTOR SIZE	1" x 3/4", 2 1/2" x 7/8"
T.D.	89.9M	DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM	MUD+WATER	FIRST READING	86.6M
FLUID LEVEL	38.9M	RESIST. SCALE (Ω/DIV.)	2
DRILLER		S.P. SCALE (MV/DIV.)	1.5
INTERPRETATION DATA		PROBE SIZE	1 5/8"
PROBE N°	C1	RES. TYPE	SINGLE POINT
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME	7 μsec		
OPERATOR	W. MCG.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY




GEOEX
PTY. LTD.

LOGGING DATA

DATE 10.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 107.0M	
REGION NUNJIKOMPITA		RANGE 40CPD	
PROJECT		TIME CONSTANT 2SEC	
HOLE DATA		LOGGING SPEED 7M/MIN	
HOLE N° IR 492		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 50CPD	
CASING		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
T.D. 109.5M		DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MUD+WATER		FIRST READING 106.6M	
FLUID LEVEL 17.8M		RESIST. SCALE (M/DIV.) 1.5	
DRILLER		S.P. SCALE (MY/DIV.) 1.5	
INTERPRETATION DATA		PROBE SIZE 1 9/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7µSEC			
OPERATOR W.MFG.			
REMARKS			
GAMMA RAY		S. P.	
		RESISTIVITY	



DATE 10.6.80

Hand-drawn geophysical log on grid paper. The vertical axis represents depth in feet, ranging from 0 to 70. The horizontal axis at the top has two scales: 'ORE SCALE' (0 to 600 CPS) and 'LITH SCALE' (0 to 400 CPS). The log shows two main curves: 'SP SCALE (MV)' and 'RESISTIVITY SCALE (Ω)'. The 'SP SCALE' curve starts at 0 MV at the surface, remains relatively flat until about 20 feet, then shows a significant negative deflection (downward) reaching a minimum of approximately -55 MV at 55 feet depth, before rising back towards 0 MV. The 'RESISTIVITY SCALE' curve starts at 1.5 Ω at the surface, remains relatively flat until about 20 feet, then shows a significant positive deflection (upward) reaching a maximum of approximately 1.5 Ω at 55 feet depth, before rising back towards 1.5 Ω. A 'FLUID LEVEL' is marked at approximately 35 feet depth. The log is drawn on a grid with major lines every 5 feet and minor lines every 1 foot.

LOGGING DATA


DATE 10.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNJIKOMPITA		FIRST READING 82.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2SEC	
HOLE NO. IR 494		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 40CPS	
T.D. 84.7M		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 1/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 20.6M		FIRST READING 81.6M	
DRILLER		RESIST. SCALE (M/DIV.) 1.5	
INTERPRETATION DATA		S.P. SCALE (M/DIV.) 1.5	
PROBE NO. C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7.0SEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 6.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 82.0M	
REGION NUNSIKOMPITA		RANGE 40 CPD	
PROJECT		TIME CONSTANT 2 SEC	
HOLE DATA		LOGGING SPEED 7 M/MIN	
HOLE N° IR 473		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 60 CPS	
CASING		DETECTOR SIZE 1" x 3/4" x 2 1/2" x 7/8"	
T.D. 84.8M		DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MUD+WATER		FIRST READING 81.6M	
FLUID LEVEL 25.3M		RESIST. SCALE (M/DIV.) 2.5	
DRILLER		S.P. SCALE (MV/DIV.) 3	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 MSEC			
OPERATOR W.M.G.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 6-6-80

LOCATION		GAMMA RAY	
STATE	SA		
REGION	NUNTIKOMPITA	FIRST READING	82.0M
PROJECT		RANGE	40 CPS
HOLE DATA		TIME CONSTANT	2 SEC
HOLE N°	IR 474	LOGGING SPEED	7 M/MIN
HOLE SIZE	4 3/4"	PAPER SCALE	100:1
CASING		BACKGROUND COUNTS	60 CPS
T.D.	84.6M	DETECTOR SIZE	1" x 3/4" x 2 1/2" x 7/8"
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	6.0M	FIRST READING	81.6M
DRILLER		RESIST. SCALE (V/DIV.)	2.5
INTERPRETATION DATA		S.P. SCALE (MY/DIV.)	3
PROBE N°	C1	PROBE SIZE	1 5/8"
CALIBRATION STANDARD		RES. TYPE	SINGLE POINT
'K' FACTOR		RIG TIME	
DEAD TIME	7 MSEC		
OPERATOR	W.MCG.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 6.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNJIKOMPITA		FIRST READING 95.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2SEC	
HOLE N° IR 475		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 200 CPS	
T.D. 97.4M		DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 1/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 47.7M		FIRST READING 94.6M	
DRILLER		RESIST. SCALE (V/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MY/DIV.) 3	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA

DATE 5.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NUNSIKOMPITA	FIRST READING 52.0M
PROJECT	RANGE 40CPD
HOLE DATA	TIME CONSTANT 2SEC
HOLE NO IR 470	LOGGING SPEED 7M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 100 CPS
T.D. 54.7M	DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD + WATER	ELECTRIC
FLUID LEVEL 16.8M	FIRST READING 51.6M
DRILLER	RESIST. SCALE (Ω/DIV.) 2.5
INTERPRETATION DATA	S.P. SCALE (MV/DIV.) 2
PROBE NO C1	PROBE SIZE 1 3/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7μSEC	
OPERATOR W.MCG.	
REMARKS	

GAMMA RAY

S. P.

RESISTIVITY

0 200 400 600 CPS
ORE SCALE0 200 400 600 CPS
LITH SCALE2
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40

45

50

FLUID LEVEL

MANUAL PEN SHIFT

MANUAL PEN SHIFT

19.1

LOGGING DATA

DATE 5.6.80

LOCATION		GAMMA RAY	
STATE	SA		
REGION	NWNIKOMPITA	FIRST READING	70.0M
PROJECT		RANGE	40cps
HOLE DATA		TIME CONSTANT	2 sec
HOLE N°	IR 471	LOGGING SPEED	7 M/MIN
HOLE SIZE	4 3/4"	PAPER SCALE	100:1
CASING		BACKGROUND COUNTS	30 cps
T.D.	73.0M	DETECTOR SIZE	1" x 3/4" ; 2 1/2" x 7/8"
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	11.6M	FIRST READING	69.6M
DRILLER		RESIST. SCALE (M/DIV.)	2.5
INTERPRETATION DATA		S.P. SCALE (MV/DIV.)	2
PROBE N°	C1	PROBE SIZE	1 5/8"
CALIBRATION STANDARD		RES. TYPE	SINGLE POINT
'K' FACTOR		RIG TIME	
DEAD TIME	7 μsec		
OPERATOR	W.MCG.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

0 200 400 600 cps

ORE SCALE

0 200 400 600 cps

LITH SCALE

2
SP SCALE (MV)2.5
RESISTIVITY SCALE

0

5

10

15

20

25

30

35

40

45

50

55

60

65

70

FLUID LEVEL

MANUAL PEN SHIP

LOGGING DATA

DATE 6.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 64.0M	
REGION NUNSIKOMPITA		RANGE 40 CPS	
PROJECT		TIME CONSTANT 2 SEC	
HOLE DATA		LOGGING SPEED 7 M/MIN	
HOLE N° IR 472		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 80 CPS	
CASING		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
T.D. 66.7M		DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MWD+WATER		FIRST READING 63.6M	
FLUID LEVEL 11.8M		RESIST. SCALE (Ω/DIV.) 2.5	
DRILLER		S.P. SCALE (MV/DIV.) 3	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 μSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

472

0 200 400 600 CPS
ORE SCALE0 200 400 600 CPS
LITH SCALE3
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40

45

50

55

60

65

FLUID LEVEL

MANUAL PEN SHIFT

MANUAL PEN SHIFT

LOGGING DATA


DATE 7.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NLINJIKOMPITA		FIRST READING 50.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE NO. IR 478		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 20 CPS	
T.D. 52.4M		DETECTOR SIZE 1' x 3/4'; 2 1/2' x 7/8'	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 11.5M		FIRST READING 49.6M	
DRILLER		RESIST. SCALE (V/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE NO. C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 MSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 7.6.80

LOCATION		GAMMA RAY	
STATE	SA		
REGION	NUNTIKOMPITA	FIRST READING 58.0M	
PROJECT		RANGE 40 CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N°	IR 479	LOGGING SPEED 7 M/MIN	
HOLE SIZE	4 3/4"	PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 60 CPS	
T.D.	60.7M	DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	11.6M	FIRST READING 57.6M	
DRILLER		RESIST. SCALE (~DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 2	
PROBE N°	C1	PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME	7 µsec		
OPERATOR	W. McG.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA

DATE 7.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NLINJIKOMPITA		FIRST READING 70.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N° IR 476b		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 100CPD	
T.D. 72.4M		DETECTOR SIZE 1" x 3/4", 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 9.1M		FIRST READING 69.6M	
DRILLER		RESIST. SCALE (X/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 µSEC			
OPERATOR W.M.C.G.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

476b

0 200 400 600
ORE SCALE0 200 400 600
LITH SCALE3
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40

45

MANUAL PEN SHIP

50

55

60

65

70

FLUID LEVEL

MANUAL PEN SHIP

LOGGING DATA

DATE 6.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNJIKOMPITA		FIRST READING 40.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2SEC	
HOLE N° IR 477		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 100CPS	
T.D. 42.6M		DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 6.4M		FIRST READING 39.6M	
DRILLER		RESIST. SCALE (V/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 3	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W.MEG			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

0 200 400 600 CPS

ORE SCALE

0 200 400 600 CPS

LITH SCALE

3
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40

FLUID LEVEL

MANUAL PEN SHIFT

LOGGING DATA


DATE 31.5.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NLNJKOMPITA		FIRST READING 22.0M	
PROJECT		RANGE 40 CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE N° IR 444		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 100 CPS	
T.D. 24.1M		DETECTOR SIZE 1"x 3/4"; 2 1/2"x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM DRY HOLE.		ELECTRIC	
FLUID LEVEL —		FIRST READING	
DRILLER		RESIST. SCALE (Ω/DIV.) —	
INTERPRETATION DATA		S. P. SCALE (MY/DIV.) —	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.


RESISTIVITY



LOGGING DATA

DATE 1.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNTIKOMPITA		FIRST READING 49.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE NO: IR 447		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 80 CPS	
T.D. 51.4M		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD + WATER		ELECTRIC	
FLUID LEVEL 7.7M		FIRST READING 48.6M	
DRILLER		RESIST. SCALE (~ / DIV.) 5	
INTERPRETATION DATA		S. P. SCALE (MY / DIV.) 3	
PROBE NO: C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 uSec			
OPERATOR W.M.C.G.			
REMARKS			
GAMMA RAY		S. P.	
		RESISTIVITY	




DATE 1.6.80

LOCATION		GAMMA RAY	
STATE	SA	FIRST READING	33.0M
REGION	NUNTUKOMPITA	RANGE	40 CPD
PROJECT		TIME CONSTANT	2 SEC
HOLE DATA		LOGGING SPEED	7 M/MIN
HOLE N°	IR 446	PAPER SCALE	IND 11
HOLE SIZE	4 3/4"	BACKGROUND COUNTS	120 cps
CASING		DETECTOR SIZE	1" x 3/4"; 2 1/2" x 7/8"
T.D.	35.9 M	DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM	MUD + WATER	FIRST READING	32.6 M
FLUID LEVEL	21.0 M	RESIST. SCALE (1/DIV.)	2
DRILLER		S.P. SCALE (MY/DIV.)	3
INTERPRETATION DATA		PROBE SIZE	1 5/8"
PROBE N°	C1	RES. TYPE	SINGLE POINT
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME	7 μSEC		
OPERATOR	W.M.G.		
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY




DATE 31.5.80

LOCATION	GAMMA RAY
STATE SA	
REGION NUNTIKOMPITA	FIRST READING 22.0M
PROJECT	RANGE 40 CPD
HOLE DATA	TIME CONSTANT 2 SEC
HOLE NO. IR 445	LOGGING SPEED 7M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 60 CPS
T.D. 24.2M	DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MWD + WATER	ELECTRIC
FLUID LEVEL 3.8M	FIRST READING 21.6M
DRILLER	RESIST. SCALE (r/DIV.) 2
INTERPRETATION DATA	S.P. SCALE (MY/DIV.) 2
PROBE NO. C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 μsec	
OPERATOR W.McG.	
REMARKS	

GAMMA RAY

S P

RESISTIVITY



LOGGING DATA

DATE 3.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 93.0M	
REGION NUNTIKOMPITA		RANGE 40CPD	
PROJECT		TIME CONSTANT 2 SEC	
HOLE DATA		LOGGING SPEED 7 M/MIN	
HOLE N° IR 460		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 50 CPS	
CASING		DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 1/8"	
T.D. 95.2M		DIGITAL READ OUT ✓	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MUD+WATER		FIRST READING 92.6M	
FLUID LEVEL 57.8M		RESIST. SCALE (Ω/DIV.) 2.5	
DRILLER		S.P. SCALE (MV/DIV.) 3	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 μSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

0 200 400 600 CPS

ORE SCALE

0 200 400 600

LITH SCALE

3
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40

45

50

55

60

65

70

75

80

85

90

95

FLUID LEVEL

LOGGING DATA

DATE 4.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNJIKOMPITA		FIRST READING 52.0M	
PROJECT		RANGE 40CPD	
HOLE DATA			
HOLE NO: IR 461		TIME CONSTANT 2SEC	
HOLE SIZE 4 3/4"		LOGGING SPEED 7M/MIN	
CASING		PAPER SCALE 100:1	
T.D. 54.7M		BACKGROUND COUNTS 20cps	
SURFACE ELEVATION		DETECTOR SIZE 1" x 3/4" x 2 1/2" x 7/8"	
BOREHOLE MEDIUM MUD + WATER		DIGITAL READ OUT	
FLUID LEVEL 16.2		ELECTRIC	
DRILLER		FIRST READING 51.6M	
		RESIST. SCALE (M/DIV.) 2.5	
INTERPRETATION DATA			
PROBE NO: C1		S.P. SCALE (M/DIV.) 3	
CALIBRATION STANDARD		PROBE SIZE 1 5/8"	
'K' FACTOR		RES. TYPE SINGLE POINT	
DEAD TIME 7 μSEC		RIG TIME	
OPERATOR W.MFG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

461

0 200 400 600 cps

ORE SCALE

0 200 400 600 cps

WITH SCALE

600 cps

3
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40

45


50

FLUID LEVEL

LOGGING DATA


DATE 4.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NLINJIKOMPITA	FIRST READING 68.0M
PROJECT	RANGE 40CPD
HOLE DATA	TIME CONSTANT 2SEC
HOLE N° TR462	LOGGING SPEED 7 M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 40cps
T.D. 70.7M	DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD + WATER	ELECTRIC
FLUID LEVEL 18.3M	FIRST READING 67.6M
DRILLER	RESIST. SCALE (~/DIV.) 2.5
INTERPRETATION DATA	S.P. SCALE (MY/DIV.) 3
PROBE N° C1	PROBE SIZE 1 9/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 μSEC	
OPERATOR W.MCG.	
REMARKS	
GAMMA RAY	S. P.
	RESISTIVITY



LOGGING DATA

DATE 4.6.80

[illegible]

LOGGING DATA

DATE 4.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNTIKOMPITA		FIRST READING 46.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2 SEC	
HOLE NO. IR 467		LOGGING SPEED 7 M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 140 CPS	
T.D. 48.2M		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 9.2M		FIRST READING 45.6M	
DRILLER		RESIST. SCALE (Ω/DIV.) 2.5	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 2	
PROBE NO. C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W.McG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY

467

0 200 400 600 CPS
ORE SCALE0 200 400 600 CPS
LITH SCALE2
SP SCALE (MV)2.5
RESISTIVITY SCALE (Ω)

0

5

10

15

20

25

30

35

40


45

FLUID LEVEL

DATE 4.6.80

LOCATION		GAMMA RAY
STATE SA		FIRST READING 43.0M
REGION NUNJIKOMPITA		RANGE 40CPD
PROJECT		TIME CONSTANT 2SEC
HOLE DATA		LOGGING SPEED 7 M/MIN
HOLE NO IR 46A		PAPER SCALE 100:1
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 40 CPS
CASING		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 3/8"
T.D. 45.4'		DIGITAL READ OUT
SURFACE ELEVATION		ELECTRIC
BOREHOLE MEDIUM MUD + WATER		FIRST READING 42.6M
FLUID LEVEL 13.8M.		RESIST. SCALE (~ / DIV.) 2.5
DRILLER		S.P. SCALE (MY / DIV.) 3
INTERPRETATION DATA		PROBE SIZE 1 5/8"
PROBE NO C1		RES. TYPE SINGLE POINT
CALIBRATION STANDARD		RIG TIME
'K' FACTOR		
DEAD TIME 7 μsec		
OPERATOR W.M.G.		
REMARKS		

GAMMA RAY
S. P.
RESISTIVITY



LOGGING DATA


DATE 4.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NLNJIKOMPITA	FIRST READING 52.0m
PROJECT	RANGE 40 CPD
HOLE DATA	TIME CONSTANT 2 SEC
HOLE NO: IR 465	LOGGING SPEED 7 M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 40 CPS
T.D. 54.4m	DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD+WATER	ELECTRIC
FLUID LEVEL 15.8m	FIRST READING 51.6m
DRILLER	RESIST. SCALE (Ω/DIV.) 2.5
INTERPRETATION DATA	S.P. SCALE (MV/DIV.) 2
PROBE NO: C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 μSEC	
OPERATOR W.M.G.	
REMARKS	


GAMMA RAY

S. P.

RESISTIVITY



DATE 4.6.80

[illegible]

LOGGING DATA


DATE 4.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NLNJKOMPITA	FIRST READING 23.0M
PROJECT	RANGE 40CPD
HOLE DATA	TIME CONSTANT 2SEC
HOLE NO. IR 468	LOGGING SPEED 7M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 100CPS
T.D. 30.7M	DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD+WATER	ELECTRIC
FLUID LEVEL 13.1M	FIRST READING 27.6M
DRILLER	RESIST. SCALE (M/DIV.) 2.5
INTERPRETATION DATA	S.P. SCALE (MV/DIV.) 2
PROBE NO. C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7μSEC	
OPERATOR W.MCG.	
REMARKS	


GAMMA RAY

S. P.

RESISTIVITY




DATE 5.6.80

[illegible]

LOGGING DATA


DATE 8.6.80

LOCATION		GAMMA RAY	
STATE	SA		
REGION	NUNSIKOMPITA	FIRST READING	70.0M
PROJECT		RANGE	40CPD
HOLE DATA		TIME CONSTANT	2SEC.
HOLE N°	IR 489	LOGGING SPEED	7M/MIN
HOLE SIZE	4 3/4"	PAPER SCALE	100:1
CASING		BACKGROUND COUNTS	80CPS
T.D.	72.6M	DETECTOR SIZE	1" x 3/4"; 2 1/2" x 7/8"
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	24.5M	FIRST READING	69.6M
DRILLER		RESIST. SCALE (K/DIV.)	2
INTERPRETATION DATA		S.P. SCALE (MV/DIV.)	1.5
PROBE N°	C1	PROBE SIZE	1 5/8"
CALIBRATION STANDARD		RES. TYPE	SINGLE POINT
'K' FACTOR		RIG TIME	
DEAD TIME	7 μsec		
OPERATOR	W.M.G.		
REMARKS			
GAMMA RAY		S. P.	RESISTIVITY



LOGGING DATA

DATE 9.6.80

[illegible]

LOGGING DATA


DATE 8.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 76.0m	
REGION NUNTIKOMPITA		RANGE 40 CPS	
PROJECT		TIME CONSTANT 2 SEC	
HOLE DATA		LOGGING SPEED 7m/min	
HOLE N° IR 486		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 50 CPS	
CASING		DETECTOR SIZE 1" x 3/4" x 2 1/2" x 1/8"	
T.D. 73.9		DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MLID+WATER		FIRST READING 75.6m	
FLUID LEVEL 17.2m		RESIST. SCALE (m/DIV.) 2	
DRILLER		S.P. SCALE (mV/DIV.) 1.5	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 mSec			
OPERATOR W.M.G.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 8.6.80

LOCATION		GAMMA RAY	
STATE SA		FIRST READING 94.0M	
REGION NUNSIKOMPITA		RANGE 40CPD	
PROJECT		TIME CONSTANT 2 SEC.	
HOLE DATA		LOGGING SPEED 7 M/MIN	
HOLE N° IR 485		PAPER SCALE 100:1	
HOLE SIZE 4 3/4"		BACKGROUND COUNTS 50 CPS	
CASING		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
T.D. 96.8M		DIGITAL READ OUT	
SURFACE ELEVATION		ELECTRIC	
BOREHOLE MEDIUM MUD+WATER		FIRST READING 93.6M	
FLUID LEVEL 10.9M		RESIST. SCALE (M/DIV.) 1	
DRILLER		S.P. SCALE (MY/DIV.) 1.5	
INTERPRETATION DATA		PROBE SIZE 1 5/8"	
PROBE N° C1		RES. TYPE SINGLE POINT	
CALIBRATION STANDARD		RIG TIME	
'K' FACTOR			
DEAD TIME 7 MSEC			
OPERATOR W.MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY



LOGGING DATA


DATE 8.6.80

LOCATION		GAMMA RAY	
STATE	SA		
REGION	NUNSIKOMPITA	FIRST READING	46.0M
PROJECT		RANGE	40CPD
HOLE DATA		TIME CONSTANT	2SEC
HOLE N°	IR 484	LOGGING SPEED	7M/MIN
HOLE SIZE	4 3/4"	PAPER SCALE	100:1
CASING		BACKGROUND COUNTS	80CPS
T.D.	48.5M	DETECTOR SIZE	1" x 3/4" ; 2 1/2" x 7/8"
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM	MUD+WATER	ELECTRIC	
FLUID LEVEL	27.6M	FIRST READING	45.6M
DRILLER		RESIST. SCALE (Ω/DIV.)	1
INTERPRETATION DATA		S.P. SCALE (MV/DIV.)	1.5
PROBE N°	C1	PROBE SIZE	1 5/8"
CALIBRATION STANDARD		RES. TYPE	SINGLE POINT
'K' FACTOR		RIG TIME	
DEAD TIME	7 μSEC		
OPERATOR	W.MCG.		
REMARKS			

GAMMA RAY

S. P.


RESISTIVITY



DATE 8.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NUNSIKOMPITA	FIRST READING 52.0M
PROJECT	RANGE 40 CPD
HOLE DATA	TIME CONSTANT 2 SEC
HOLE NO. IR 487	LOGGING SPEED 7 M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 80 CPB
T.D. 54.2M	DETECTOR SIZE 1" x 3/4" x 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD+WATER	ELECTRIC
FLUID LEVEL 13.1M	FIRST READING 51.6M
DRILLER	RESIST. SCALE (r/DIV.) 2
INTERPRETATION DATA	S.P. SCALE (MY/DIV.) 1.5
PROBE NO. C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 USEC	
OPERATOR W.M.G.	
REMARKS	

GAMMA RAY
S. P.
RESISTIVITY



LOGGING DATA

DATE 8.6.80


LOCATION		GAMMA RAY	
STATE SA			
REGION NLINJIKOMPITA		FIRST READING 58.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2SEC	
HOLE N° IR 483		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 30CPS	
T.D. 60.3M		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+ WATER		ELECTRIC	
FLUID LEVEL 23.4M		FIRST READING 57.6M	
DRILLER		RESIST. SCALE (V/DIV.) 1	
INTERPRETATION DATA		S.P. SCALE (MY/DIV.) 1.5	
PROBE N° C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 MSEC			
OPERATOR W. MCG.			
REMARKS			

GAMMA RAY

S. P.

RESISTIVITY


483



DATE 7.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NLNJIKOMPITA	FIRST READING 46.0M
PROJECT	RANGE 40CPD
HOLE DATA	TIME CONSTANT 2 SEC
HOLE NO. TR 481	LOGGING SPEED 7 M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 80CPD
T.D. 48.6M	DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MUD+WATER	ELECTRIC
FLUID LEVEL 1.6M	FIRST READING 45.6M
DRILLER	RESIST. SCALE (r/DIV.) 2.5
INTERPRETATION DATA	S.P. SCALE (MY/DIV.) 3
PROBE NO. C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 USEC	
OPERATOR W.MCG	
REMARKS	


GAMMA RAY
S. P.
RESISTIVITY



LOGGING DATA

DATE 8.6.80

LOCATION		GAMMA RAY	
STATE SA			
REGION NUNJIKOMPITA		FIRST READING 46.0M	
PROJECT		RANGE 40CPD	
HOLE DATA		TIME CONSTANT 2SEC	
HOLE NO. IR 482		LOGGING SPEED 7M/MIN	
HOLE SIZE 4 3/4"		PAPER SCALE 100:1	
CASING		BACKGROUND COUNTS 60CPG	
T.D. 48.4M		DETECTOR SIZE 1" x 3/4"; 2 1/2" x 7/8"	
SURFACE ELEVATION		DIGITAL READ OUT	
BOREHOLE MEDIUM MUD+WATER		ELECTRIC	
FLUID LEVEL 15.1M		FIRST READING 45.6M	
DRILLER		RESIST. SCALE (Ω/DIV.) 2	
INTERPRETATION DATA		S.P. SCALE (MV/DIV.) 2	
PROBE NO. C1		PROBE SIZE 1 5/8"	
CALIBRATION STANDARD		RES. TYPE SINGLE POINT	
'K' FACTOR		RIG TIME	
DEAD TIME 7 μSEC			
OPERATOR W.MCG.			
REMARKS			
GAMMA RAY		S. P.	
		RESISTIVITY	



LOGGING DATA

DATE 7.6.80

LOCATION	GAMMA RAY
STATE SA	
REGION NIUNJIKOMPITA	FIRST READING 46.0M
PROJECT	RANGE 40 CPD
HOLE DATA	TIME CONSTANT 2 SEC
HOLE N° IR 480	LOGGING SPEED 7 M/MIN
HOLE SIZE 4 3/4"	PAPER SCALE 100:1
CASING	BACKGROUND COUNTS 60 CPS
T.D. 48.5M	DETECTOR SIZE 1" x 3/4" ; 2 1/2" x 7/8"
SURFACE ELEVATION	DIGITAL READ OUT
BOREHOLE MEDIUM MWD+WATER	ELECTRIC
FLUID LEVEL 13.5M	FIRST READING 45.6M
DRILLER	RESIST. SCALE (r/DIV.) 2.5
INTERPRETATION DATA	S.P. SCALE (MY/DIV.) 2
PROBE N° C1	PROBE SIZE 1 5/8"
CALIBRATION STANDARD	RES. TYPE SINGLE POINT
'K' FACTOR	RIG TIME
DEAD TIME 7 WSEC	
OPERATOR W.MCG.	
REMARKS	

GAMMA RAY
S. P.
RESISTIVITY

