

**SOUTH AUSTRALIA**  
**DEPARTMENT OF MINES AND ENERGY**



**OPEN FILE ENVELOPE NO. 8428**

**EL 1698, PIONEER DAM**

**PROGRESS AND FINAL REPORTS FOR THE PERIOD**  
**14/2/91 TO 13/8/92**

**Submitted by**

**CRA Exploration Pty Ltd**

**1992**

**© South Australian Department of Mines and Energy: 11/5/93**

This report was supplied as part of the requirement to hold a mineral or petroleum exploration tenement in the State of South Australia. The Department accepts no responsibility for statements made, or conclusions drawn, in the report or for the quality of original text or drawings.

All rights reserved under the copyright. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the written permission of the S.A. Department of Mines and Energy, P.O. Box 151, Eastwood, S.A. 5063.

# ENVELOPE 8428

**TENEMENT:** EL 1698, Pioneer Dam

**TENEMENT HOLDER:** CRA Exploration Pty Ltd

## CONTENTS

<b>REPORT:</b>	<b>Mackee, G.L., 1991. First quarterly report for Pioneer Dam EL 1698, South Australia, for the period ending 13 May, 1991. (CRAE report no. 17300).</b>	<b>SADME NO.</b>	
<b>PLANS</b>		<b>8428 R 1</b>	
		<b>Pgs 3-10</b>	
	<b>Scale      Company</b>		
	<b>Plan no.</b>		
Location plan.	1:250 000    SAa 5392	Pg. 10	A3
Base map.	1:100 000    SAa 5488	8428-1	
Aeromagnetic contour plan.	1:100 000    SAa 5489	8428-2	
Bouguer gravity contours.	1:100 000    SAa 5538	8428-3	
<b>REPORT:</b>	<b>Mackee, G.L., 1991. Second quarterly report for Pioneer Dam EL 1698, South Australia, for the period ending 13th August, 1991 (CRAE report no. 17478).</b>	<b>8428 R 2</b>	
<b>PLANS</b>		<b>Pgs 11-18</b>	
	<b>Scale      Company</b>		
	<b>Plan no.</b>		
Location map.	1:250 000    SAa 5392	Pg. 18	A3
Base map	1:100 000    SAa 5488	8428-1	
Aeromagnetic contour plan.	1:100 000    SAa 5489	8428-2	
Bouguer gravity contours with interpreted faults.	1:100 000    SAa 5538	8428-4	
<b>REPORT:</b>	<b>Mackee, G.L., 1991. Third quarterly report for Pioneer Dam EL 1698, South Australia, for the period ending 13th November, 1991 (CRAE report no. 17688).</b>	<b>8428 R 3</b>	
<b>PLANS</b>		<b>Pgs 19-26</b>	
	<b>Scale      Company</b>		
	<b>Plan no.</b>		
Location map.	1:250 000    SAa 5392	Pg. 26	A3
Confidence Bore Prospect DD1PD1.	1:500        SAa 5642	8428-5	
Base map.	1:100 000    SAa 5488	8428-1	
<b>REPORT:</b>	<b>Mackee, G.L., 1992. Fourth quarterly report for Pioneer Dam EL 1698, South Australia, for the period ending 13th February, 1992 (CRAE report no. 17957).</b>	<b>8428 R 4</b>	
<b>APPENDIX 1:</b>	<b>Drillhole DD92PD1 bore logs.</b>	<b>Pgs 27-33</b>	
<b>PLANS</b>		<b>Pgs 34-46</b>	
	<b>Scale      Company</b>		
	<b>Plan no.</b>		
Location plan.	1:250 000    SAa 5392	Pg. 47	A3
Base map.	1:100 000    SAa 5488	8428-6	
<b>Billeroo West Prospect:</b>			
Lines 13000N, 14000N, 15000N. TMI profiles.	1:25 000      SAa 5702	8428-7	
Bouguer gravity and TMI profile Line 10000ME.	1:10 000      SAa 5703	8428-8	
<b>REPORT:</b>	<b>Mackee, G.L., 1992. EL 1698 Pioneer Dam, S.A. Fifth quarterly report for the period ended 13th May, 1992.</b>	<b>8428 R 5</b>	
		<b>Pg. 48</b>	

**REPORT:** Mackee, G.L., 1992. Sixth quarterly and final report for Pioneer Dam EL 1698,  
South Australia, for the period ending 13th August, 1992 (CRAE report no. 18264).

**PLANS**

	Scale	Company Plan no.
Location plan.	1:250 000	SAa 5392
Base map.	1:100 000	SAa 5488

**SADME NO.**  
**8428 R 6**  
Pgs 49-58

Pg. 56  
8428-6

A3

## END OF CONTENTS

## SEPARATELY HELD DATA

### DRILLHOLE SAMPLES (held by SADME Core Library):


For up to date information on available drillhole samples, contact the Supervisor, SADME Core Library and quote the Exploration Licence and drillhole number/s you wish to query.

CRA EXPLORATION PTY. LIMITED

FIRST QUARTERLY REPORT FOR  
PIONEER DAM EL 1698, SOUTH AUSTRALIA,  
FOR THE PERIOD ENDING 13 MAY, 1991

AUTHOR: G.L. MACKEE  
COPIES TO: SADME  
CIS CANBERRA  
DATE: 28TH MAY, 1991  
SUBMITTED BY: *M. Donnelly*  
For G.L. MACKEE  
ACCEPTED BY: *[Signature]*

"ALL RIGHTS IN THIS REPORT AND ITS CONTENTS (INCLUDING RIGHTS TO CONFIDENTIAL INFORMATION AND COPYRIGHT IN TEXT, DIAGRAMS AND PHOTOGRAPHS) REMAIN WITH CRA AND NO USE (INCLUDING REPRODUCTION, STORAGE OR TRANSMISSION) MAY BE MADE OF THE REPORT OR ITS CONTENTS FOR ANY PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF CRA.  
CRA EXPLORATION PTY. LIMITED 1988"



17300

CONTENTSPAGE

## LIST OF PLANS

1. SUMMARY	1
2. CONCLUSIONS AND RECOMMENDATIONS	1
3. INTRODUCTION	1
4. WORK COMPLETED	1
4.1 Landholders	1
4.2 Geophysics	2

EXPENDITURE	3
-------------	---

LOCATION	4
----------	---

KEYWORDS	4
----------	---

LIST OF PLANS

<u>Plan No.</u>	<u>Title</u>	<u>Scale</u>
SAa 5392	Pioneer Dam EL 1698 - S.A., Location Plan	1:250 000
SAa 5488	Pioneer Dam EL 1698 - S.A., Base Map	1:100 000
SAa 5489	Pioneer Dam EL 1698 - S.A., Aeromag Contour Plan	1:100 000
SAa 5538	Pioneer Dam EL 1698 - S.A., Regional Gravity Contours	1:100 000

## 1. SUMMARY

Pioneer Dam EL 1698 was granted to CRA Exploration Pty. Limited on 14th February, 1991 for a period of one year. The area is considered to have potential for base-metal mineralisation of both Mississippi Valley and Roxby Downs styles.

During the first quarter, notices of entry were sent to the major lease holders and compilation of geophysical data started. The gravity plan was upgraded using SADME's digital database, and structural re-interpretation commenced. A consequence of this work has highlighted the need to assess available open-file seismic data.

## 2. CONCLUSIONS AND RECOMMENDATIONS

- Some platformal basement areas adjacent to interpreted faulting may be conducive to MVT base-metal mineralisation.
- Available open-file seismic traverses over these areas should be acquired and inspected to assist structural interpretation.

## 3. INTRODUCTION

Pioneer Dam EL 1698 was applied for and subsequently granted on 14th February, 1991 for a period of one year. The licence covers an area of approximately 1425 square km and is located 130 km north of Olary on land held under several pastoral leases (plans SAa 5392 and SAa 5488).

The EL area has previously been explored for Tertiary Uranium and Roxby Downs Style targets by Pacminex/Esso (SML's 268/267, 543/544, EL's 45/42, 59, 109) from 1971-74, Mines Administration (EL 171) from 1975-76, C.S.R. Limited (EL's 227, 411, 722, 1065, 1487) from 1976-1990.

CRA Exploration selected the area for investigation of Roxby Downs style targets and possible MVT base-metal mineralisation.

## 4. WORK COMPLETED

### 4.1 Landholders

Title searches were completed and Notices of Entry sent to the major pastoral lease holders.

#### 4.2 Geophysics

Plans at 1:100 000 scale of regional aeromagnetics and gravity were compiled (SAa 5489 and SAa 5538). The regional gravity database was improved through the purchase of the S.A.D.M.E. digital gravity data base which incorporates substantial detailed traverses along petroleum exploration seismic lines. Several detailed gravity grids over Roxby-style magnetic anomalies were also acquired from open-file data, but these have not been incorporated into the data set since they are not tied in to the regional data.

Structural interpretation of the geophysical data is not yet complete, but preliminary investigations suggest a series of fault-bounded basement platforms which have been tilted into half-grabens by the north-west trending MacDonald, Strathearn and Benagerie Faults. Open-file seismic sections will be inspected to assist in the structural interpretation.

*M. Donnelly*

FOR G.L. MACKEE

G.L. MACKEE

GLM/dt



EXPENDITURE

Expenditure on Pioneer Dam EL 1698 for the period ending 30th April, 1991, the nearest accounting period, amounted to \$13,380.00, as detailed below.


	\$
Payroll & Benefits	4 338
Field & Transport	3 742
Contractors	500
General Administration & Office	2 584
Overheads	2 213
Rounding	<u>3</u>
<b>Total</b>	<b>\$13 380</b>

LOCATION

Curnamona	SH54-14	1:250 000 sheet
Pasmore	6835	1:100 000 sheet
Benagerie	6935	1:100 000 sheet
Curnamona	6834	1:100 000 sheet
Kalabity	6934	1:100 000 sheet

KEYWORDS

Geophys Gravity, Geophys Magnetism, Base Metals



CRA EXPLORATION PTY LIMITED

# PIONEER DAM ELA - S.A. LOCATION PLAN

Approx. Area 1425 Km<sup>2</sup>

REF. CURNAMONA SH 54-14


SCALE 1 : 250000

AUTHOR G.L.M.

DATE July '90

REPORT 17300

PLAN No SAa 5392




8428-1


CRA EXPLORATION PTY. LIMITED

PIONEER DAM E.L. 1698 - S.A.  
BASE MAP

REFERENCE: CURNAMONA SH 5a-14	
SCALE: 1:100000	DRAWN: F.R.
AUTHOR: G.L.M.	REPORT: 17300
DATE: JAN. 1991	PLAN NO. 5a 5488








CRA EXPLORATION PTY. LIMITED	
PIONEER DAM EL. - S.A.	
AEROMAGNETIC CONTOUR PLAN	
REFERENCE: CURNAMONA SH 54-14	
SCALE: 1:100 000	DRAWN: F.R.
AUTHOR: G.L.M.	REPORT: 17300
DATE: JAN. 1991	PLAN NO. 5Aa 5489




8428-3



8428-3

C.R.A. EXPLORATION PTY LIMITED	
PIONEER DAM EL 1698 - S.A.	
BOUGUER GRAVITY CONTOURS	
REF. CURNAMONA SH 54-14	
SCALE 1:100000	
AUTHOR: G. L. M.	REPORT: 17300
DATE: 9/ 5/ 91	PLAN NO.: 5 A a 5538





## CRA EXPLORATION PTY LIMITED

**SUBJECT:** SECOND QUARTERLY REPORT FOR PIONEER DAM EL 1698,  
SOUTH AUSTRALIA, FOR THE PERIOD ENDING  
13TH AUGUST, 1991

**AUTHOR:** G.L. MACKEE

**DATE:** 16TH AUGUST, 1991

"All rights in this report and its contents (including rights to confidential information and copyright in text, diagrams and photographs) remain with CRA Exploration and no use (including use of reproductions, storage or transmission) may be made of the report or its contents for any purpose without the prior written consent of CRA Exploration. © CRA Exploration Pty. Limited 1988."

CRA EXPLORATION PTY. LIMITED

SECOND QUARTERLY REPORT FOR  
PIONEER DAM EL 1698, SOUTH AUSTRALIA,  
FOR THE PERIOD ENDING 13TH AUGUST, 1991

AUTHOR: G.L. MACKEE

COPIES TO: SADME  
CIS CANBERRA

DATE: 16TH AUGUST, 1991

SUBMITTED BY:

ACCEPTED BY:

The block contains two handwritten signatures. The first signature, above the 'SUBMITTED BY:' label, appears to be 'M. G. Mackee'. The second signature, above the 'ACCEPTED BY:' label, is more stylized and illegible.

"ALL RIGHTS IN THIS REPORT AND ITS CONTENTS (INCLUDING RIGHTS TO CONFIDENTIAL INFORMATION AND COPYRIGHT IN TEXT, DIAGRAMS AND PHOTOGRAPHS) REMAIN WITH CRA AND NO USE (INCLUDING REPRODUCTION, STORAGE OR TRANSMISSION) MAY BE MADE OF THE REPORT OR ITS CONTENTS FOR ANY PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF CRA.

© CRA EXPLORATION PTY. LIMITED 1988"



CONTENTSPAGE

## LIST OF PLANS

1. SUMMARY	1
2. INTRODUCTION	1
3. WORK COMPLETED	1
3.1 Geophysical Interpretation	1
3.2 Drilling	2

EXPENDITURE	3
-------------	---

LOCATION	4
----------	---

KEYWORDS	4
----------	---

LIST OF PLANS

<u>Plan No.</u>	<u>Title</u>	<u>Scale</u>
SAa 5392	Pioneer Dam EL 1698 - S.A., Location Plan	1:250 000
SAa 5488	Pioneer Dam EL 1698 - S.A., Base Map	1:100 000
SAa 5489	Pioneer Dam EL 1698 - S.A., Aeromag Contour Plan	1:100 000
SAa 5538	Pioneer Dam EL 1698 - S.A., Regional Gravity Contours with Interpreted Faults	1:100 000

## 1. SUMMARY

Interpretation of regional geophysical data within the EL suggests a series of fault bounded basement platforms have been tilted into a series of half grabens. One such platformal area has been selected for drill-testing to establish the presence of a sufficient thickness of Cambrian carbonates to host Mississippi Valley type Pb/Zn mineralisation.

Approval for the proposed drill hole of up to 400 metres depth has been granted by the South Australian Department of Mines and Energy. The hole is planned to commence during the next quarter.

## 2. INTRODUCTION

Pioneer Dam EL 1698 was applied for and subsequently granted on 14th February, 1991 for a period of one year. The licence covers an area of approximately 1425 square km and is located 130 km north of Olary on land held under several pastoral leases (plans SAa 5392 and SAa 5488).

The EL area has previously been explored for Tertiary Uranium and Roxby Downs Style targets by Pacminex/Esso (SML's 268/267, 543/544, EL's 45/42, 59, 109) from 1971-74, Mines Administration (EL 171) from 1975-76, C.S.R. Limited (EL's 227, 411, 722, 1065, 1487) from 1976-1990.

CRA Exploration selected the area for investigation of Roxby Downs style targets and possible MVT base-metal mineralisation. This report details the activities to the end of the Second Quarter, ending 13th August, 1991.

## 3. WORK COMPLETED

### 3.1 Geophysical Interpretation

The structural interpretation of the regional gravity and magnetic data has resulted in a series of tilted basement blocks being defined (plans SAa 5489 and 5538). Existing drill holes ETM5 and BWM1 (plan SAa 5488) show Cambrian sediments to be thinning out against a basement dome to the east of the EL. An interpreted down thrown platform west of the Strathearn Fault in the Confidence Bore area retains the potential of a shallow, thick sequence of Cambrian carbonates. The structural setting of these adjacent intersecting major fault systems further enhances the potential for a mineralised system to be present.

To the NW, the Cambrian carbonates become increasingly deep beneath the younger sediments of the Arrowie Basin.

### 3.2 Drilling

An exploration drill hole is planned within the above area to test for Mississippi Valley Pb/Zn mineralisation. The pastoral lease holder has been served with a Notice of Use of Declared Equipment and approval for the hole has been sought and granted by SADME.



G.L. MACKEE

GLM/dt

EXPENDITURE

Expenditure on Pioneer Dam EL 1698 for the period ending 31st July, 1991, the nearest accounting period, amounted to \$8 622.00, as detailed below.


	\$
Payroll & Benefits	3 174
Field & Transport	1 066
District Administration	3 044
Regional Overheads	<u>1 338</u>
<b>Total</b>	<b>\$8 622</b>


LOCATION

Curnamona	SH54-14	1:250 000 sheet
Pasmore	6835	1:100 000 sheet
Benagerie	6935	1:100 000 sheet
Curnamona	6834	1:100 000 sheet
Kalabity	6934	1:100 000 sheet

KEYWORDS

Geophys Gravity, Geophys Magnetism, Base Metals






8428-1


CRA EXPLORATION PTY. LIMITED

PIONEER DAM E.L. 1698 - S.A.  
BASE MAP

REFERENCE	CURNAMONA SH 5a-14
SCALE	1:100000
AUTHOR	G.L.M.
DATE	JAN. 1991
DRAWN	F.R.
REPORT	17300
PLAN NO.	5a 5488







CRA EXPLORATION PTY. LIMITED	
PIONEER DAM EL. - S.A.	
AEROMAGNETIC CONTOUR PLAN	
REFERENCE: CURNAMONA SH 54-14	
SCALE: 1:100 000	DRAWN: F.R.
AUTHOR: G.L.M.	REPORT: 17300
DATE: JAN. 1991	PLAN NO. SA 5489



8428-4



Interpreted Fault

8428-4

C.R.A. EXPLORATION PTY LIMITED

PIONEER DAM EL 1698 - S.A.

BOUGUER GRAVITY CONTOURS  
WITH INTERPRETED FAULTS

REF. CURNAMONA SH 54-14

SCALE 1:100000


AUTHOR: G. L. M.

DATE: 9/ 5/ 91

REPORT: 17478

PLAN NO.: S.A. 5538

SCALE 1:100000



CRA EXPLORATION PTY. LIMITED

THIRD QUARTERLY REPORT FOR  
PIONEER DAM EL 1698, SOUTH AUSTRALIA,  
FOR THE PERIOD ENDING 13TH NOVEMBER, 1991

AUTHOR: G.L. MACKEE  
COPIES TO: SADME  
CIS CANBERRA  
DATE: 28TH NOVEMBER, 1991  
SUBMITTED BY:  
ACCEPTED BY:

*J. L. Mackee*  
*[Signature]*

"ALL RIGHTS IN THIS REPORT AND ITS CONTENTS (INCLUDING RIGHTS TO CONFIDENTIAL INFORMATION AND COPYRIGHT IN TEXT, DIAGRAMS AND PHOTOGRAPHS) REMAIN WITH CRA AND NO USE (INCLUDING REPRODUCTION, STORAGE OR TRANSMISSION) MAY BE MADE OF THE REPORT OR ITS CONTENTS FOR ANY PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF CRA.  
© CRA EXPLORATION PTY. LIMITED 1988"

CONTENTSPAGE

## LIST OF PLANS

1. SUMMARY	1
2. CONCLUSIONS AND RECOMMENDATIONS	1
3. INTRODUCTION	1
4. WORK COMPLETED	1
4.1 Drilling	1
4.2 Geophysical Logging	2

EXPENDITURE	3
-------------	---

LOCATION	4
----------	---

KEYWORDS	4
----------	---

LIST OF PLANS

<u>Plan No.</u>	<u>Title</u>	<u>Scale</u>
SAa 5392	Pioneer Dam EL 1698 - S.A., Location Plan	1:250 000
SAa 5488	Pioneer Dam EL 1698 - S.A., Base Map	1:100 000
SAa 5642	Pioneer Dam EL 1698 - Confidence Bore Prospect DD91PD1	1:500

## 1. SUMMARY

Drillhole DD91PD1 was completed to 409 metres depth to test for the presence of Cambrian Carbonate lithologies with Mississippi Valley Base Metal potential. No significant thicknesses of carbonate were encountered.

Further work should await results of geochemical assay of selected intervals from the drillhole.

## 2. CONCLUSIONS AND RECOMMENDATIONS

- A significant thickness of shallow Cambrian carbonate lithologies is not present in the Confidence Bore area.
- Further work in the area should await results of the geochemical assays from the core, particularly in the interval 150 - 200 metres where a significant SP anomaly was detected during geophysical logging of DD91PD1.

## 3. INTRODUCTION

Pioneer Dam EL 1698 was applied for and subsequently granted on 14th February, 1991 for a period of one year. The licence covers an area of approximately 1425 square km and is located 130 km north of Olary on land held under several pastoral leases (plans SAa 5392 and SAa 5488).

The EL area has previously been explored for Tertiary Uranium and Roxby Downs Style targets by Pacminex/Esso (SML's 268/267, 543/544, EL's 45/42, 59, 109) from 1971-74, Mines Administration (EL 171) from 1975-76, C.S.R. Limited (EL's 227, 411, 722, 1065, 1487) from 1976-1990.

CRA Exploration selected the area for investigation of Roxby Downs style targets and possible MVT base-metal mineralisation. This report details the activities to the end of the Third Quarter, ending 13th November, 1991.

## 4. WORK COMPLETED

### 4.1 Drilling

Hole DD91PD1 was sited at 405050 mE/6531000 mN on the Confidence Bore Prospect as a result of geophysical structural interpretation of available regional magnetic and gravity data (refer Second Quarterly Report). The location is shown on plan SAa 5488.

A 140 metre pre-collar was completed by the S.A. Department of Mines and Energy using rotary-mud techniques. This pre-collar was cased with 100mm steel casing and pressure grouted to conform with SADME requirements to ensure no interconnection of Quaternary/Tertiary aquifers with underlying aquifers. Silver City Drilling of Broken Hill, NSW completed the diamond-cored hole to 409 metres total depth.

A summary of the drillhole is as follows:-

Summary Log of DD91PD1 - Pioneer Dam EL 1698

<u>Depth (m)</u>	<u>Description</u>
0 - 6	Sand.
6 - 120	Clays, grey/green to brown with occ. thin bands of sand. Base of Cainozoic?
120 - 214	Red/Brown micaceous, calcareous laminated siltstone with vughs and fractures mostly clay filled, occasionally calcite filled. Rare sulphides.
214 - 309	Red/brown micaceous laminated siltstone/shale with common thin bands of white evaporite. No vughs.
309 - 319	Brown, very micaceous, competent sandstone and dolomite.
319 - EOH	Interbedded shale, dolomite and sandstone, very micaceous, lamellae from ,1mm to 20cm at 90 deg. to LCA.

All magnetic susc. readings in range 0.00005 SI to 0.00030 SI.  
All Scintillometer readings in range 50 to 70 cps (Scintrex BGS-4).

Hole surveyed at 409 metres - 4.5 deg. off vertical at 125 degrees.

A fully detailed log of hole DD91PD1 will be presented when assays and petrological results are available.

#### 4.2 Geophysical Logging

DD91PD1 was geophysically logged approximately one month after hole completion, with natural gamma, single point resistance and self-potential parameters recorded - refer plan SAa 5642.

The natural gamma response was uniformly low throughout most of the hole, with minor peaks over the intervals 6 - 21 metres and at 54 metres. A significant S.P. anomaly of -160 mV is present over the interval 150 - 200 metres. The cause of the anomaly is not know, and assays and petrological studies of the core are awaited.

A magnetic susceptibility log of the hole was abandoned due to technical problems, but regular measurements on the chips and core indicate no susceptibilities in excess of 0.00030 SI units.

*J. L. Mackee*

G.L. MACKEE

GLM/tt

EXPENDITURE

Expenditure on Pioneer Dam EL 1698 for the period 1st August, 1991 to 31st October, 1991 amounted to \$74,477 as detailed below.

	\$
Payroll & Benefits	8,930.00
Drilling	47,067.00
Field & Transport	4,632.00
Computer Services	805.00
Office Supplies	111.00
District Administration	8,760.00
Regional Overheads	4,172.00
<b>Total</b>	<b>74,477.00</b>

---




LOCATION


Curnamona	SH54-14	1:250 000 sheet
Pasmore	6835	1:100 000 sheet
Benagerie	6935	1:100 000 sheet
Curnamona	6834	1:100 000 sheet
Kalabity	6934	1:100 000 sheet

KEYWORDS

Geophys Gravity, Geophys Magnetism, Base Metals, Drill Rotary, Drill Diamond, Geophys Borehole, Cambrian.




8428-5



8428-5

CRA EXPLORATION PTY LIMITED			
PIONEER DAM EL 1698			
CONFIDENCE BORE PROSPECT			
DD91PD1			
REFERENCE CURNAMONA SH 54-14			
SCALE	1:500	DRAWN	DGP
AUTHOR	GLM	REPORT	17688
DATE	26 NOV 91	PLAN No	SAa 5642




8428-1

CRA EXPLORATION PTY. LIMITED

PIONEER DAM E.L.1698 - S.A.  
BASE MAP

REFERENCE	CURNAMONA SH 5a-14
SCALE	1:100000
AUTHOR	G.L.M.
DATE	JAN. 1991
DRAWN	F.R.
REPORT	17300
PLAN NO.	5a 5488





**CRA EXPLORATION PTY LIMITED**

**SUBJECT:                      FOURTH QUARTERLY REPORT FOR  
                                    PIONEER DAM EL 1698, SOUTH AUSTRALIA  
                                    FOR THE PERIOD ENDING 13TH FEBRUARY, 1992**

**AUTHOR:            G L MACKEE**

**DATE:                30TH MARCH, 1992**

**"All rights in this report and its contents (including rights to confidential information and copyright in text, diagrams and photographs) remain with CRA Exploration and no use (including use of reproductions, storage or transmission) may be made of the report or its contents for any purpose without the prior written consent of CRA Exploration. © CRA Exploration Pty. Limited 1988."**

**CRAE REPORT NO: 17957**

CRA EXPLORATION PTY. LIMITED

FOURTH QUARTERLY REPORT FOR  
PIONEER DAM EL 1698, SOUTH AUSTRALIA,  
FOR THE PERIOD ENDING 13TH FEBRUARY, 1992

AUTHOR: G.L. MACKEE  
COPIES TO: SADME  
CIS CANBERRA  
DATE: 30TH MARCH, 1992  
SUBMITTED BY: *J.L. Mackee*  
ACCEPTED BY: *[Signature]*

"ALL RIGHTS IN THIS REPORT AND ITS CONTENTS (INCLUDING RIGHTS TO CONFIDENTIAL INFORMATION AND COPYRIGHT IN TEXT, DIAGRAMS AND PHOTOGRAPHS) REMAIN WITH CRA AND NO USE (INCLUDING REPRODUCTION, STORAGE OR TRANSMISSION) MAY BE MADE OF THE REPORT OR ITS CONTENTS FOR ANY PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF CRA.  
© CRA EXPLORATION PTY. LIMITED 1988"

CRA Report # 17957

CONTENTSPAGE

LIST OF PLANS

LIST OF APPENDICES

1. SUMMARY 1

2. INTRODUCTION 1

3 WORK COMPLETED 1

3.1 Drilling 1

3.2 Geophysical Logging 2

EXPENDITURE 3

LOCATION 4

KEYWORDS 4

LIST OF PLANS

<u>Plan No.</u>	<u>Title</u>	<u>Scale</u>
SAa 5392	Pioneer Dam EL 1698 - S.A., Location Plan	1:250 000
SAa 5488	Pioneer Dam EL 1698 - S.A., Base Map	1:100 000
SAA 5702	Pioneer Dam EL 1698 - Billeroo West Prospect Lines 13000N, 14000N, 15000N - T.M.I. Profiles	1: 10 000
SAa 5703	Pioneer Dam EL 1698 - Billeroo West Prospect Line 10,000 mE - Bouguer Gravity and T.M.I. Profiles	1: 25 000

LIST OF APPENDICES

Appendix I    Drillhole DD91PD1 - Borehole Logs.



## 1. SUMMARY

Interpretation of lithologies encountered in drillhole DD91PD1 indicates the hole failed to penetrate the targetted early Cambrian sediments. Geochemical assays of the middle Cambrian lithologies encountered between 140 and 409 metres did not realise any significant values.

A second prospect area, Billeroo West, was selected for further investigations several km to the SE of DD91PD1 where the Strathearn Fault approaches a basement high and shallower lower Cambrian sediments may be expected. Ground magnetic and gravity traversing has been completed in this area to locate the fault and allow depth modelling of a basement-related cross-cutting magnetic anomaly.

The western part of EL 1698 has been relinquished. The remaining area was renewed for a further 12 months.

## 2. INTRODUCTION

Pioneer Dam EL 1698 was applied for and subsequently granted on 14th February, 1991 for a period of one year. The licence covers an area of approximately 1425 square km and is located 130 km north of Olary on land held under several pastoral leases (plans SAa 5392 and SAa 5488).

The EL area has previously been explored for Tertiary Uranium and Roxby Downs Style targets by Pacminex/Esso (SML's 268/267, 543/544, EL's 45/42, 59, 109) from 1971-74, Mines Administration (EL 171) from 1975-76, C.S.R. Limited (EL's 227, 411, 722, 1065, 1487) from 1976-1990.

CRA Exploration selected the area for investigation of Roxby Downs style targets and possible MVT base-metal mineralisation. This report details the activities to the end of the Fourth Quarter, ending 13th February, 1992.

## 3 WORK COMPLETED

### 3.1 Drilling

All geochemical assays for drillhole DD91PD1 have been received. They are fully detailed in Appendix I in the final drillhole logs for DD91PD1. No significant base or precious metal assays were detected. In particular, no elevated geochemical results were detected over the interval 150 to 200 metres, where a strong S.P. anomaly was detected (Third Quarterly Report). The S.P. anomaly is possibly caused by aquifers of differing salinity.

Inspection of the core from DD91PD1 indicates the lithologies intersected are consistent with the middle Cambrian Balcoracana or Billy Creek Formations. The target basal Cambrian carbonates are not present in the hole.

As a result of the above, the potential for shallow lower Cambrian carbonates to the west of DD91PD1 is considered low. Accordingly, the western part of EL 1698 has been relinquished, with the remainder being retained for a further 12 months (refer Plan SAa 5392 for the retained area).

### 3.2 Geophysical Logging

Billeroo West Prospect was selected several kilometres to the S-E of DD91PD1, where the Strathearn Fault traverses the edge of a basement high lying to the N-E.

In this area, a cross-cutting linear magnetic anomaly may indicate a favourable structure for the formation of Mississippi Valley type mineralisation.

Inspection of the core from DD91PD1 indicates the lithologies intersected are consistent with the middle Cambrian Balcoracana or Billy Creek Formations. The target basal Cambrian carbonates are not present in the hole.

As a result of the above, the potential for shallow lower Cambrian carbonates to the west of DD91PD1 is considered low. Accordingly, the western part of EL 1698 has been relinquished, with the remainder being retained for a further 12 months (refer Plan SAa 5392 for the retained area).

A 12 km traverse of 100 metre spaced gravity stations was emplaced across the Strathearn Fault zone in this area to assist in location and possibly modelling of the fault structure (Plans SAa 5703 and SAa 5488). Additionally, three orthogonal traverses of 10 metre spaced ground magnetics were completed to detail the magnetic anomaly (Plan SAa 5702). Initial modelling of the magnetics suggests a depth to magnetic (?pre-Adelaidean) basement of 450 to 550 metres. Further modelling of the gravity and magnetics data is to be carried out.

*J.L. Mackee*

G.L. MACKEE

GLM/tt

EXPENDITURE

Expenditure on Pioneer Dam EL 1698 for the period ending January 1992, the nearest accounting period, amounted to \$6,943.00, as detailed below.

	\$
Payroll & Benefits	2,632.00
Drilling	(5,212.00)
Laboratory	2,000.00
Field and Transport	3,413.00
District Administration	2,917.00
Regional Overheads	1,193.00
<b>Total</b>	<b>6,943.00</b>

---

LOCATION

Curnamona	SH54-14	1:250 000 sheet
Pasmore	6835	1:100 000 sheet
Benagerie	6935	1:100 000 sheet
Curnamona	6834	1:100 000 sheet
Kalabity	6934	1:100 000 sheet

KEYWORDS

Geophys Gravity, Geophys Magnetics, Base Metals, Drill Rotary, Drill Diamond, Geophys Borehole, Cambrian.

APPENDIX I

Drillhole DD92PD1

Borehole Logs

DIAMOND DRILL LOG  
PIONEER DAM EL 1698

HOLE DD91PD1

CONFIDENCE BORE PROSPECT

MAPSHE CURNAMONA SH 54-14, BENAGERIE 6935										DPO P53062		CASING LEFT							
AZIMUTH		N/A		EASTING		405050		COMMENCED		10/1/91		OPENHOLE		0 - 140.0 m		DPO		CASING LEFT	
INCLINATION		-90		NORTHING		6531000		COMPLETED		10/10/91		HQ		140.0 - 141.1 m		DPO		WATER TABLE	
TOTAL DEPTH		409 m		RL		Approx 60 m		GEOLOGIST		GLM/MJD		NQ		141.1 - 409.0 m		DPO		OXIDISED TO	
CORE BLOCKS					GEOLOGICAL DESCRIPTION														
From	To	Rec	%Rec	Log	From	To	Summary	Detail						Sample No	From	To	Int (m)	Rec	
					0	1	SAND	Brown surficial sand							0	2			
					1	6		Poorly consolidated, fine sand with ~25% clay. Sample is orange-brown and calcareous.							2	4			
								4-6 contains 5% gypsum.							4	6			
					6	8	CLAY	Grey/Brown Clay - 10% qtz sand							6	8			
					8	10		Grey Clay - 10% qtz sand							8	10			
					10	12		Grey Clay - 10% qtz sand							10	12			
					12	14		Grey Clay							12	14			
					14	16		14-15 well rounded coarse qtz sand to 1mm grain size							14	16			
								15-16 stiff grey and brown clay with 10% coarse qtz sand.							16	18			
					16	18		Stiff, interlayered brown and grey clay; approx 5% coarse qtz sand, poss. contamination from uphole							18	20			
					18	20		Grey and Brown clay as above							20	22			
					20	22		20-20.5 as above; at 20.5m grey/white calcareous band with 1-2% black min. ?MnO							22	24			
								By 22m into stiff white clay							24	26			
					22	24		Stiff white clay with thin layers brown and grey clay. ? some silcrete contamination							26	28			
					24	26		Stiff white clay, some hard white and grey/green clay fragments							28	30			
					26	28		As above, occ. black mineral (?MnO) in grey/green clay							30	32			
					28	30		Stiff grey clay. Occasional black mineral- weathered to clay partly							32	34			
					30	32		As above							34	36			
					32	34		As above							36	38			
					34	36		As above							38	40			
					36	38		As above							40	42			
					38	40		As above - occ. fragments hard black mineral to 1cm							42	44			
					40	42		As above - occ. fragments hard black mineral to 1cm							44	46			
								dark grey clay content increasing							46	48			
					42	44		As above - mostly medium grey clay							48	50			
					44	46		As above - mostly medium grey clay							50	52			
					46	48		As above - mostly medium grey clay							52	54			
					48	50		As above - mostly medium grey clay							54	56			
					50	52		As above - mostly medium grey clay											
					52	54		As above - mostly medium grey clay											
					54	56		Green clay similar to above											
					56	58		Grey /green clay as above											



DIAMOND DRILL LOG  
PIONEER DAM EL 1698

CONFIDENCE BORE PROSPECT

HOLE DD91PD1					CONFIDENCE BORE PROSPECT										
MAPSHE CURNAMONA SH 54-14, BENAGERIE 6935										DPO	P53062		CASING LEFT		
AZIMUTH		N/A		EASTING	405050		COMMENCED	10/1/91		OPENHOLE	0 - 140.0 m		DPO	CASING LEFT	
INCLINATION		-90		NORTHING	6531000		COMPLETED	10/10/91		HQ	140.0 - 141.1 m		DPO	WATER TABLE	
TOTAL DEPTH		409 m		RL	Approx 60 m		GEOLOGIST	GLM/MJD		NQ	141.1 - 409.0 m		DPO	OXIDISED TO	
CORE BLOCKS					GEOLOGICAL DESCRIPTION										
From	To	Rec	%Rec	Log	From	To	Summary	Detail			Sample No	From	To	Int (m)	Rec
					58	60	CLAY	Grey/green clay as above				58	60		
					60	62	As above					60	62		
					62	64	As above plus a sand -band. Poor recovery					62	64		
					64	66	As above					64	66		
					66	68	As above					66	68		
					68	70	As above					68	70		
					70	72	70-71 clay dark grey, 71> as above					70	72		
					72	74	grey/green clay as above					72	74		
					74	76	As above					74	76		
					76	78	As above					76	78		
					78	80	As above					78	80		
					80	82	As above - occ. fragments of harder brown clay					80	82		
					82	84	As above - occ. frags of harder brown clay					82	84		
					84	86	As above - occ. frags of harder brown clay. ?carbonaceous					84	86		
							plus occasional hard white fragments - calcareous layers?;					86	88		
							reacts with HCl. Also 5-10% yellow clay.					88	90		
					86	88	As above, but greatly reduced recovery. Gritty fine white clay					90	92		
							present - probably most of interval.					92	94		
					88	90	80% soft off-white sludgy clay + 20% stiff grey clay.					94	96		
							V. occasional rounded qtz grain to 2mm					96	98		
					90	92	95% soft off-white to lt. brown clay with v. fine grit (carbonaceous)					98	100		
							5% hard grey nodules clay ?carbonaceous					100	102		
					92	94	90% soft lt. brown clay sludge; 10% dk. brown-lt. grey hard clay nodules					102	104		
					94	96	90% soft lt. brown and red/brown clay sludge. Occ. hard fragments					104	106		
							of red/brown clay and carbonaceous clay fragments					106	108		
					96	98	As above					108	110		
					98	100	As above; increasing % of red/brown clay to 80%					110	112		
					100	102	As above, but 90% red/brown soft-stiff clay. 5% lt. brown/white; 5% hard grey					112	114		
							nodules					114	116		
					102	104	Soft red-brown clay with occ. nodules harder grey clay								
					104	106	As above, nodules to 10%								
					106	108	As above								
					108	110	As above								
					110	112	As above								
					112	114	As above								
					114	116	As above - nodules only 1-2%								



[illegible]

DIAMOND DRILL LOG  
PIONEER DAM EL 1698

CONFIDENCE BORE PROSPECT

HOLE DD91PD1										CONFIDENCE BORE PROSPECT										DPO		P53062		CASING LEFT	
MAPSHE CURNAMONA SH 54-14, BENAGERIE 6935																				DPO				CASING LEFT	
AZIMUTH		N/A		EASTING		405050		COMMENCED		10/1/91		OPENHOLE		0 - 140.0 m		DPO				CASING LEFT					
INCLINATION		-9.0		NORTHING		6531000		COMPLETED		10/10/91		HQ		140.0 - 141.1 m		DPO				WATER TABLE					
TOTAL DEPTH		409 m		RL		Approx 60 m		GEOLOGIST		GLM/MJD		NQ		141.1 - 409.0 m		DPO				OXIDISED TO					
CORE BLOCKS					GEOLOGICAL DESCRIPTION																				
From	To	Rec	%Rec	Log	From	To	Summary	Detail				Sample No	From	To	Int (m)	Rec									
					116	118	CLAY	As above					116	118											
					118	120		As above					118	120											
					120	122	SILTSTONE	As above, but with Indurated frags - 5 % laminated flakes of (predominantly)					120	122											
								brown and grey ?mudstone. Slight/rare reaction to HCl - ?calcareous					122	124											
					122	124		Predominantly brown and grey flake of siltstone mudstone - Indurated					124	126											
								v. finely micaceous layers in laminations. Slightly calcareous					126	128											
					124	126		As above					128	130											
					126	128		As above					130	132											
					128	130		As above					132	134											
					130	132		As above					134	136											
					132	134		As above					136	138											
					134	136		As above					138	140											
					136	138		As above																	
					138	140		As above				End of pre-collar 12.00 noon. 2/10/91													



[illegible]

DIAMOND DRILL LOG  
PIONEER DAM EL 1698

CONFIDENCE BORE PROSPECT

HOLE DD91PD1

MAPSHE CURNAMONA SH 54-14, BENAGERIE 6935

AZIMUTH	N/A	EASTING	405050	COMMENCED	10/1/91	OPEN HOLE	0 - 140.0 m	DFO	P53062	CASING LEFT
INCLINATION	-90	NORTHING	6531000	COMPLETED	10/10/91	HQ	140.0 - 141.1 m	DFO		CASING LEFT
TOTAL DEPTH	409 m	RL	Approx 60 m	GEOLOGIST	GLM/MJD	HQ	141.1 - 409.0 m	DFO		WATER TABLE
CORE BLOCKS										OXIDISED TO

CORE BLOCKS							GEOLOGICAL DESCRIPTION							
From	To	Rec	%Rec	Log	From	To	Summary	Detail	Sample No	From	To	Int (m)	Rec	
					140	214	SILTSTONE	General Description: Red-brown, micaceous, calcareous, laminated siltstone-stone-shale, very fine laminations, bedding approx horizontal exhibiting	1159912	140	145	5		
								iting local undulations/ripple marks, minor slumping, micro brecciation)	1159913	145	150	5		
								tion) & cross-bedding.	1159914	150	155	5		
								Vugh common up to 1cm size, occ. containing	1159915	155	160	5		
								calcitc rem ains, but mostly clay filled.	1159916	160	165	5		
								V. fine sulphide common in fractures parallel to bedding,	1159917	165	170	5		
								across bedding and in some vughs. ?pyrite.	1159918	170	175	5		
								Fine white calcareous laminae common (acid reaction)	1159919	175	180	5		
								parallel to bedding and also in fractures	1159920	180	185	5		
								Clay seams parallel to bedding also common up to 3cm,	1159921	185	190	5		
								containing brecciated host rock & occ. sulphides	1159922	190	195	5		
					140.7	140.8		Vertical fracture with v.fine dissem. pyrite coating.	1159923	195	200	5		
					142.27			Approx. 1cm Vugh with v.fine silver-grey lining of ?sulphide	1159924	200	205	5		
					145.55	145.57		Green alteration cutting across laminae, with some blebs of	1159925	205	210	5		
								calcite in fractures.	1159926	210	215	5		
					151.6	151.62		Calcareous green clay (crumbles on exposure to air), trace py.						
					154.6	155.35		Laminated, micaceous, v.fine green beds grading downwards						
								to m. grained sandstone, interbedded with red beds;						
								Includes a 5cm clay band with brecciated fragments						
								host from 155.15 to 155.20m						
					156.1	156.2		As above, but no s/stone & includes clay rich rubble at base						
					161.7	163.05		Interbedded green and red beds, carbonate rich in upper						
								parts?						
					166	166.5		As above, limey green claystone interbedded with red beds;						
								trace sulphides on fractures.						
					170.1	170.25		As above, includes 6cm central coarse sandstone with						
								clay matrix and 1-2% black, shiny mineral grains??						
					190.5	190.7		Limey green beds, laminated, strong acid reaction on						
								clayey lamination breaks - grades downwards to red beds						
					190.7	214		Repetitive sequences of interbedded red and green beds; red						
								beds becoming more vughy, almost honeycombed in places						
								with remains of calcite material in vughs.						
								Includes at 211.15 - 211.30m a m.g. green layered zone						
								?? possible volcanics. Similar layer at 218.10 - 218.15m.						

DIAMOND DRILL LOG  
PIONEER DAM EL 1698

HOLE DD91PD1

CONFIDENCE BORE PROSPECT

MAPSHE CURNAMONA SH 54-14, BENAGERIE 6935

CORE BLOCKS					GEOLOGICAL DESCRIPTION					DPO P53062					CASING LEFT
From	To	Rec	%Rec	Log	From	To	Summary	Detail	Sample No	From	To	Int (m)	Rec		CASING LEFT
					214	309.45	SHALE	GENERAL DESCRIPTION: Core is more competent; still largely laminated red-brown micaceous shale, but with no vughs of clay seams.	1159927	215	220	5			
								Common bands of clear to white evaporitic mineral	1159928	220	225	5			
								(? anhydrite) up to 3cm. These mineral bands	1159929	225	230	5			
								occur both parallel to bedding and cross-cutting, and	1159930	230	235	5			
								include brecciated fragments of host lithology.	1159931	235	240	5			
								Hardness is similar to finger-nail and crumbles into	1159932	240	245	5			
								elongate, needle-shaped crystals.	1159933	245	250	5			
					308.56	308.59	SANDSTONE	Coarse ? sandstone composed of pink/white	1159934	250	255	5			
								rounded grains in green ? calcareous matrix.	1159935	255	260	5			
								Medium grained feldspathic sdsinterbed with minor calcareous matrix.	1159936	260	265	5			
								Feldspar grains subangular. Frags of Gn and Pu-6n shale incorporated in band.	1159937	265	270	5			
								Possible evidence of bioturbation (sub-vert. burrows) @ 307.46, 308.14-309.13m.	1159938	270	275	5			
309.45	319.3	9.85						GENERAL DESCRIPTION: Brown, very micaceous, competent sandstone with	1159939	275	280	5			
								alternating zones of horizontal laminations (bedding) and	1159940	280	285	5			
								cross-bedded with highly disrupted bedding caused	1159941	285	290	5			
								by slumping or high energy depositional environment.	1159942	290	295	5			
319.3	324.64	5.34						Laminated, very micaceous, horizontally bedded ? sandstone. Rare	1159943	295	300	5			
								thin (<1mm) white evaporitic bands.	1159944	300	305	5			
								Micro-scale disruptions to laminae.	1159945	305	310	5			
324.64	324.69	0.05						band of f.g. grey ? claystone.	1159946	310	315	5			
324.69								As for 319.3-324.64, but colour becoming more grey and	1159947	315	320	5			
								rock quite hard.	1159948	320	325	5			
307	310	3.02			309.45	319.24	S/STONE and SANDSTONE AND DOLOMITE		1159949	325	330	5			
	313	3					DOLOMITE	Brown, very micaceous, competent, fine grained sandstone. Contains brown	1159950	330	335	5			
	316	2.99						mudstone lamellae, lighter coloured dolomite bands of 0.5 -4cm thickness. Sdst	1159951	335	340	5			
	319	2.96						contains minor carbonate. Slumping and cross-bedding present. Anhydrite bands	1159952	340	345	5			
	322	3.04						no longer present.	1159953	345	350	5			
	325	2.96							1159954	350	355	5			
	328	3.01			319.24	364.09	SHALE/DOLO	INTERBEDDED SHALE, DOLOMITE AND SANDSTONE	1159955	355	360	5			
	331	2.98					and S/STONE	Both brown and green shale(50%) interbedded with grey-white dolomite	1159956	360	365	5			
	334	2.96						(35%) and brown fine grained non-calcareous sandstone (15%).							
	337	3.03						Dolomite is impure, with shale lamellae, fine sand and muscovite. Brown shal is							
	340	2.93						micaceous. Bedding thicknesses vary from 1mm to 20 cm, typically <1cm.							
	343	3						Slumping common, cross bedding moderately common. Bedding angle is							
	346	3.07						perpendicular to core axis. Trace calcite veinlets.							



DIAMOND DRILL LOG  
PIONEER DAM EL 1698

CONFIDENCE BORE PROSPECT


HOLE DD91PD1


MAPSHE CURNAMONA SH 54-14, BENAGERIE 6935

AZIMUTH		N/A		EASTING		405050		COMMENCED		10/1/91		OPENHOLE		0 - 140.0 m		DPO		CASING LEFT	
INCLINATION		-9.0		NORTHING		6531000		COMPLETED		10/10/91		HQ		140.0 - 141.1 m		DPO		WATER TABLE	
TOTAL DEPTH		409 m		FL		Approx 60 m		GEOLOGIST		GLM/MJD		NQ		141.1 - 409.0 m		DPO		OXIDISED TO	
CORE BLOCKS				GEOLOGICAL DESCRIPTION															
From	To	Rec	%Rec	Log	From	To	Summary	Detail						Sample No	From	To	Int (m)	Rec	
	349	3.01																	
	352	2.95			364.09	373.89		GREEN SHALE Predominantly green non-calcareous shale with minor brown						1159957	365	370	5		
	355	3.06						micaceous shale and white grey dolomite lamellae and bands up to 2cm thick.											
	358	3						Green shale other than lamination does not contain sedi structures. Dolomite						1159958	370	375	5		
	361	2.99						bands exhibit slumping, cross-bedding and lenticular disrupted shapes.											
								Includes: 364.09-368.70: Green shale (95%), brown shale and dolomite (5%)						1159959	375	380	5		
361	362.1	1.21						368.70-372.28: Dolomite bands little more common (5-7%) 372.28-373.89:											
	367	4.87						Brown shale lamellae content increases to approx 10% as grading into underlying						1159960	380	385	5		
	373	5.96						unit.											
373	379	6.04												1159962	385	390	5		
	385	6.03			373.89	376.37		Brown shale and sandstone. Brown, finely laminated, non-calcareous shale (55%)											
	391	5.96						with interbedded grey fine grained sandstone (43%). Dolomite bands only 2%.						1159963	390	395	5		
	397	6.02						Bioturbation(?) structures relatively common. 0.2-1cm thick sub-vertical											
	403	6.01						burrowing through bedding. Shape is dyke-like rather than tubular. Slumping is						1159964	395	400	5		
403	409	5.9						common. Bands and lamellae almost all <1cm thick. Small amount of 2 degree											
								fine carbonate @ 375.24m.						1159965	400	405	5		
								At 406m, thin L/stone band with fossil shell fragments											
					376.37	409		INTERBEDDED SHALE, DOLOMITE AND SANDSTONE Sequence of interbedded brown						1159966	405	409	4		
								and green shale (45%), impure white-grey dolomite(35%) and fine grained											
								sandstone (20%). Shale is non-calcareous and finely laminated. Dolomite is											
								impure with varying amounts of shale lamellae, sand and muscovite. Slumping is											
								most evident in dolomite bands. Dolomite and sandstone are gradational											
								depending on amount of carbonate. Cross-bedding evident in many dolomite											
								bands.											
								Unit overall is laminated to thinly bedded. Bedding angle to core axis is											
								perpendicular. Rare hairline fracture at low angle to core axis. Interval includes:											
								384.02-386.25:- Sandy dolomite bed, only minor lamellae hence tending towards											
								massive.											
								387.89-390.35: Red-brown shale (65%) dominated interval and fine grained											
								sandstone (20%) and dolomite (15%). Dyke-like bioturbation structures are											
								common and confined to this interval. Unit is finely laminated. Lamellae are											
								wavy.											
								394.90-397.43: Dolomitic sandstone bed. Lamellae less common.											
								403.71-405.18: Zone with fractures, subparallel to core axis. Fractures coated											
								with 1mm thick vein calcite and very trace pyrite smear. Lost water circulation.											



[illegible]






CRA EXPLORATION PTY. LIMITED	
PIONEER DAM EL.1698 - S.A.	
BASE MAP	
REFERENCE: CURNAMONA SH 54-14	
SCALE: 1:100 000	DRAWN: F.R.
AUTHOR: G.L.M.	REPORT: 17957
DATE: Mar. 1992	PLAN NO: 54a 5488




8428-7



8428-7

CRA EXPLORATION PTY LTD			
PIONEER DAM EL 1698			
BILLEROO WEST PROSPECT			
LINES 13000N, 14000N, 15000N			
T.M.I. PROFILES			
REFERENCE CURNAMONA SH 54-14			
SCALE	1 : 25000	DRAWN	GLM
AUTHOR	GLM	REPORT	17957
DATE	10 FEB 92	PLAN No	SAs 5702

8428-8



8428-8

CRA EXPLORATION PTY LTD			
PIONEER DAM EL 1698			
BILLEROO WEST PROSPECT			
BOUGUER GRAVITY AND			
T.M.I. PROFILE			
LINE 10,000 mE			
REFERENCE CURNAMONA SH 54-14			
SCALE	1:10,000	DRAWN	GLM
AUTHOR	GLM	REPORT	17957
DATE	11 FEB 92	PLAN No	SAs 5703



# CRA EXPLORATION PTY LIMITED

31 Osmond Terrace Norwood 5067 South Australia

Australian Company Number 000 057 125

0048

2nd June, 1992

The Director General,  
Department of Mines & Energy, South Australia  
PO Box 151,  
EASTWOOD. S.A. 5063.

Dear Sir,

Re: EL 1698 Pioneer Dam, S.A.  
Fifth Quarterly Report For The Period Ended 13th May, 1992

No field work was undertaken during the period.

Interpretation of the geophysical survey data collected in the previous quarter is incomplete. On completion, the results from the geophysical survey will be reported.

Expenditure for the quarter ended 30th April, 1992 amounted to \$17 975.

Yours faithfully,

G.L. MACKEE  
GEOPHYSICIST

GLM/pq



**CRA EXPLORATION PTY LIMITED**

**SUBJECT:**        **SIXTH QUARTERLY AND FINAL REPORT FOR  
PIONEER DAM EL 1698, SOUTH AUSTRALIA,  
FOR THE PERIOD ENDING 13TH AUGUST, 1992**

**AUTHOR:**        **G L MACKEE**

**DATE:**            **SEPTEMBER, 1992**

**"All rights in this report and its contents (including rights to confidential information and copyright in text, diagrams and photographs) remain with CRA Exploration and no use (including use of reproductions, storage or transmission) may be made of the report or its contents for any purpose without the prior written consent of CRA Exploration. © CRA Exploration Pty. Limited 1988."**

**CRAE REPORT NO:    18264**

CRA EXPLORATION PTY. LIMITED

SIXTH QUARTERLY AND FINAL REPORT FOR  
PIONEER DAM EL 1698, SOUTH AUSTRALIA,  
FOR THE PERIOD ENDING 13TH AUGUST, 1992

AUTHOR: G L MACKEE  
COPIES TO: SADME  
CIS CANBERRA  
DATE: 8TH SEPTEMBER, 1992  
SUBMITTED BY: *J.L. Mackee*  
ACCEPTED BY: *[Signature]*

\*ALL RIGHTS IN THIS REPORT AND ITS CONTENTS (INCLUDING RIGHTS TO CONFIDENTIAL INFORMATION AND COPYRIGHT IN TEXT, DIAGRAMS AND PHOTOGRAPHS) REMAIN WITH CRA AND NO USE (INCLUDING USE OF REPRODUCTION, STORAGE OR TRANSMISSION) MAY BE MADE OF THE REPORT OR ITS CONTENTS FOR ANY PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF CRA.  
© CRA EXPLORATION PTY. LIMITED 1988\*



CONTENTSPage

## LIST OF PLANS

1. SUMMARY	1
2. INTRODUCTION	1
3. PREVIOUS WORK	1
4. WORK COMPLETED	2
5. EXPENDITURE	3
6. REFERENCES	4
7. LOCATION	4
8. KEYWORDS	4

LIST OF PLANS

<u>Plan No.</u>	<u>Title</u>	<u>Scale</u>
SAa 5392	Pioneer Dam EL 1698, SA, Location Plan	1:250 000
SAa 5488	Pioneer Dam EL 1698, SA, Base Map	1:100 000
SAa 5899	Pioneer Dam EL 1698, SA, Billeroo West Prospect Bouguer Gravity Model - Line 10 000 mE	1:100 000
SAa 5900	Pioneer Dam EL 1698, SA, Billeroo West Prospect Ground Magnetism Model - Line 14 000 mN	1: 25 000

## 1. SUMMARY

Final modelling of the gravity and magnetic data from Billeroo West prospect was completed. The model did not definitively locate the Strathearn Fault zone and no drilling target for Mississippi Valley type deposit resulted.

No further priority targets were considered to exist within the licence area and Pioneer Dam EL 1698 was surrendered on 23rd September, 1992.

## 2. INTRODUCTION

Pioneer Dam EL 1698 was applied for and subsequently granted on 14th February, 1991 for a period of one year. At the completion of the first year of tenure, the tenement reduced from 1425 square kilometres to its present 804 square kilometres (Plan SAa 5392). The licence is located 130 km north of Olary on land held under several pastoral leases.

CRA Exploration selected the area for investigation of Roxby Downs style targets and Mississippi Valley box-metal mineralisation. No work was completed during the Fifth Quarter, and this Sixth and Final Report details the activities for the period ending 13th August, 1992.

## 3. PREVIOUS WORK

The EL area has previously been explored for Tertiary Uranium and Roxby Downs Style targets by Pacminex/Esso (SML's 268/267, 543/544, EL's 45/42, 59, 109) from 1971-74, Mines Administration (EL 171) from 1975-76 and CSR Limited (EL's 227, 411, 722, 1065, 1487) from 1976-1990.

During the first quarter of CRA Exploration's tenure, compilation of regional and detailed geophysical data was completed and structural interpretation commenced (CRAE Report 17300).

Structural interpretation was completed during the second quarter and a drill site targeted to test an interpreted Rift-graben structure for the presence of lower Cambrian carbonates with MVT mineralisation (CRAE Report 17478).

In the third quarter, drill hole DD91PD1 was completed at 409 metres TD without intersecting the targeted basal Cambrian units (CRAE Report 17688).

During the fourth quarter, ground magnetic and gravity surveying was completed at the Billeroo West prospect to try to locate the Strathearn Fault tract adjacent to an interpreted basement high. Geochemical assays for DD92PD1 gave no elevated base metal values. A partial reduction in tenement was also granted (CRAE Report 17957).

No field work was completed during the fifth quarter.

#### 4. WORK COMPLETED

Final modelling of the gravity and magnetic data collected over the Billeroo West prospect was completed. No definitive fault trace in the general area of the Strathearn Fault was apparent in the model, which tended to show a gradual deepening of basement cover towards the south west, along line 10 000 mE (Plan SAa 5899). The model of the magnetic anomaly on line 14 000 mN, at about the projected location of the Strathearn Fault, shows magnetic basement to be at 500 metres depth (Plan SAa 5900). This agrees fairly well with the gravity model at this location.

Aside from the source of the magnetic anomaly itself, it is not considered that a significant MVT drilling target exists in this area.



G L MACKEE.

GLM/tt

5. EXPENDITURE

Expenditure on EL 1698 for the three month period ending 31st July, 1992 amounted to Nil.

## 6. REFERENCES

- Mackee GL, 1991 First Quarterly Report for Pioneer Dam EL 1698, SA for the Period Ending 13th May, 1991. CRAE Report No 17300.
- Mackee GL, 1991 Second Quarterly Report for Pioneer Dam EL 1698, SA for the Period Ending 13th August, 1991. CRAE Report No 17478.
- Mackee GL, 1991 Third Quarterly Report for Pioneer Dam EL 1698, SA for the Period Ending 13th November, 1991. CRAE Report No 17688.
- Mackee GL, 1992 Fourth Quarterly Report for Pioneer Dam EL 1698, SA for the Period Ending 13th February, 1992. CRAE Report No 17957.


## 7. LOCATION

Curnamona	SH 54-14	1:250 000 sheet
Pasmore	6835	1:100 000 sheet
Benagerie	6935	1:100 000 sheet
Curnamona	6834	1:100 000 sheet
Kalabity	6934	1:100 000 sheet

## 8. KEYWORDS

Geophys Gravity, Geophys Magnetism, Base Metals, Cambrian.






CRA EXPLORATION PTY. LIMITED	
PIONEER DAM EL.1698 - S.A.	
BASE MAP	
REFERENCE: CURNAMONA SH 54-14	
SCALE: 1:100 000	DRAWN: F.R.
AUTHOR: G.L.M.	REPORT: 17957
DATE: Mar. 1992	PLAN NO: 54a 5488





PIONEER DAM EL 1698  
BILLEROO WEST - LINE 10000 mE



COORDINATES:

Strike Perp 45 deg  
Line Direction 0 deg  
Scale - m 1 m

Main Direction  
Main Offset  
Cross Direction  
Cross Offset



MODEL PARAMETERS:

Model Type	X	Wedge
Depth	F	65.0 m
Thickness	F	1038 m
Half Width Top	F	3517 m
Half Width Bot	F	4026 m
Shift	F	-8087 m
Density	X	-0.250 g/cc
Main Position	F	413300.6 m
Cross Position	X	6518787 m
Base Level	F	-8.429245 mgal
Base Slope	X	0 mgal/m

(F-fitted, X-fixed, L-limit)

Report No. 18264  
Plan No. SAa 5899

PIONEER DAM EL 1698  
Billeroo West, Line 14000 mN



GEOMAGNETIC FIELD:

Field Strength 57500 nT  
Inclination -63 deg  
Declination 7 deg

COORDINATES:

Sensor Height 2 m  
Strike Perp 115 deg  
Line Direction 135 deg  
Main Direction 135 deg  
Main Offset 0 m  
Cross Direction  
Cross Offset 0 m

MODEL PARAMETERS:

Model Type		Tabular
Depth	F	500 m
Half Width	F	350 m
Dip	F	90 deg
Susceptibility	F	0.00152 emu
Remnance Ratio	X	0
Remnance Incl	X	0 deg
Remnance Decl	X	0 deg
Main Position	F	9611.701 m
Cross Position	X	14000 m
Base Level	F	57653.29 nT
Base Slope	F	.0334607 nT/m

(F-fitted, X-fixed, L-limit)

Report No. 18264  
Plan No. SAa 5900